Stormwater Quality Management Plan for Carefield Senior Care Facility

Bonsall, CA PDS2019-REZ-19-001

Prepared for:

Carefield Senior Living 201 Lomas Santa Fe Drive, Ste 450 Solana Beach, CA 92075

Prepared by:

Tory R Walker Engineering 122 Civic Center Drive, Ste 206 Vista, CA 92084

Prepared on:

February 7, 2020

Tory R. Walker, PE R.C.E. 45005





County of San Diego

Stormwater Quality Management Plan (SWQMP) For Priority Development Projects (PDPs)

Use for all PDPs (see Storm Water Intake Form, Part 5)



Project Information	
Project Name	Carefield Senior Care
Project Address	Mission Rd. & Thoroughbred Lane, Bonsall, California
Assessor's Parcel # (APN)	126-230-55-00
Permit # / Record ID	PDS2019-STP-19-005, PDS2019-REZ-19-001

Project Applicant / Project Proponent						
Name	Steve Barklis, Carefield Solana, LLC					
Address	201 Lomas Santa Fe Dr	201 Lomas Santa Fe Dr Suite 450, Solana Beach, CA 92075				
Phone	(858) 259-5591					

SWQMP Preparer					
Name	Tory R. Walker Engin	eering, Inc.			
Company (if applicable)	Company				
Address	122 Civic Center Drive, Suite 206 Vista, California 92084				
Phone	(760) 414-9212	Email: info@TRWEngineering.com			
PE Number (if applicable)	45005				

Preparer's Certification

I understand that the County of San Diego has adopted minimum requirements for managing urban runoff, including storm water, from land development activities, as described in the County of San Diego BMP Design Manual. The BMP Design Manual is a design manual for compliance with local County of San Diego Watershed Protection Ordinance (Sections 67.801 et seq.) and regional MS4 Permit (California Regional Water Quality Control Board San Diego Region Order No. R9-2013-0001, as amended by Order No. R9-2015-0001 and Order No. R9-2015-0100) requirements for storm water management.

This SWQMP is intended to comply with applicable requirements of the BMP Design Manual. I certify that it has been completed to the best of my ability and accurately reflects the project being proposed and the applicable BMPs proposed to minimize the potentially negative impacts of this project's land development activities on water quality. I understand and acknowledge that the plan check review of this SWQMP by County staff is confined to a review and does not relieve me as the person in charge of overseeing the selection and design of storm water BMPs for this project, of my responsibilities for project design.

Signature & Maken	Date	February 7, 2020
-------------------	------	------------------

COUNTY ACCEPTED

SWOMP Approved By: Name Approval Date: Date

* Note* Approval does not constitute compliance with regulatory requirements.

Template Date: December 11, 2018 Preparation Date: February 7, 2020

Submittal Record: List the dates of SWQMP and plan submittals and updates. Briefly describe key changes from previous versions. If responding to plan check comments, note this in the entry and attach the responses as applicable.

No.	Date	Summary of Changes				
Preli	Preliminary Design / Planning / CEQA					
1	3/11/2019	Initial Submittal				
2	10/23/2019	Updated per County Comments				
3	2/7/2020	Updated per County Commnets				
4	Date	Summary of Change				
No.	Date	Summary of Change				
Fina	l Design					
1	Date	Initial Submittal				
2	Date	Summary of Change				
3	Date	Summary of Change				
4	Date	Summary of Change				
No.	Date	Summary of Change				
Plan	Changes					
1	Date	Initial Submittal				
2	Date	Summary of Change				
3	Date	Summary of Change				
4	Date	Summary of Change				
No.	Date	Summary of Change				

Template Date: December 11, 2018 Preparation Date: February 7, 2020

PDP SWQMP Submittal Checklist

SWQMP Tables : All of the eight tables below must be completed.	
☑ Table 1: Scope of SWQMP Submittal	Page 2
☑ Table 2: Baseline BMPs for Existing Natural Features and Proposed Features (Groups 1, 2, and 3)	Page 3
☑ Table 3: Baseline BMPs for Pollutant-generating Sources (Group 4)	Page 4
☑ Table 4: Infeasibility Justifications for Baseline BMPs	Page 5
☑ Table 5: DMA Structural Compliance Strategies and Documentation	Page 6
☑ Table 6: Critical Coarse Sediment Yield Area (CCSYA) Requirements	Page 7
☑ Table 7: Minimum Construction Stormwater BMPs	Page 8
☑ Table 8: Infeasibility Justifications for Construction BMPs	Page 9
SWQMP Attachments ¹ : Use the checklist below to identify which attachments will be including with this submittal. Attachments with boxes already checked (\boxtimes) are required for all project The applicability of other attachments will be determined upon completing this form.	
☑ Attachment 1: Storm Water Intake Form	
☑ Attachment 2: DMA Exhibits and Construction Plan Sheets	
☑ Attachment 3: Source Control BMP Worksheet	
☐ Attachment 4: Previous SWQMP Submittals	
☑ Attachment 5: Existing Site and Drainage Description	
☑ Attachment 6: Documentation of DMAs without Structural BMPs	
oxtimes Attachment 7: Documentation of DMAs with Structural Pollutant Control BMPs	
oxtimes Attachment 8: Documentation of DMAs with Structural Hydromodification Managemen	t BMPs
\square Attachment 9: Management of Critical Coarse Sediment Yield Areas	
☑ Attachment 10: Installation Verification Form	
☑ Attachment 11: BMP Maintenance Agreements and Plans	
\square Attachment 12: Documentation of Alternative Compliance Projects (ACPs)	

After completing the remainder of this form, check the applicable SWQMP Attachment boxes to summarize your selections.

Template Date: December 11, 2018 Preparation Date: February 7, 2020

¹ All SWQMP attachments are available at www.sandiego.gov/stormwater under the Development Resources tab. Some attachments are presented out of order because they are shared between multiple SWQMP forms.

Table 1 – Scope of SWOMP Submittal

Select one option below that describes the scope of the	is SWQMP Submittal. Document your selection as indicated.
SWQMP Scope	Required Documentation
oxtimes a. SWQMP addresses the entire project	No additional documentation.
☐ b. SWQMP implements requirements of an earlier master SWQMP submittal	Include a copy of the previous submittal as Attachment 4 .
\square c. First of multiple SWQMP submittals	Use the spaces below to identify the elements addressed in this submittal and in future submittals.
(1) Elements addressed in current submittal (str	reets, common areas, first project phase, etc.):
(2) Elements to be addressed in future submittal	(s) (individual lots, future project phases, etc.):

Template Date: December 11, 2018 Preparation Date: February 7, 2020 Page | 2

Table 2 - Baseline BMPs for Existing and Proposed Site Features

Iak	nc 2 Dascille Divil 8 101	LAISTI	ig and i ropo	Scu Sitt	reatures	<u>, </u>				
	Features		BMP Implementation							
	Select each feature that applies. Describe BMP implementation for each selected site feature.									
Group 1: Existing Natural Site Features [See BMPDM Sections 4.3.1 and 4.3.2]										
		natu	in & conserve ral features (SD-G)	Establish buffers for waterbodies (SD-H)						
		Full	Partial	Full	Partial					
	Natural waterbodies									
	Natural storage reservoirs & drainage corridors									
\boxtimes	Natural areas, soils, & vegetation (incl. trees)									
Gro	up 2: Common Impervious Ou	tdoor Si	ite Features [Se	e BMPDM	Sections 4.3.	3 and 4.3.5]				
			Disperse		rmeable	Minimize	impervious			
		_	rvious areas (SD-B)		erials D-D)		eas 5D-I)			
_		Full	Partial —	Full	Partial	☐ Check here to confirm				
	Streets and roads						ious surfaces			
\boxtimes	Sidewalks & walkways					have been minimized				
\boxtimes	Parking areas & lots				\boxtimes	where applicable and feasible for all outdoor				
\boxtimes	Driveways				\boxtimes	impervious areas. If not,				
\boxtimes	Patios, decks, & courtyards					explain in Table 3.				
	Hardcourt recreation areas									
	Add impervious feature									
	Add impervious feature									
	Add impervious feature									
Gro	up 3: Other Outdoor Site Featt	ıres [See	BMPDM Section	s 4.2.6, 4.3	.4, 4.3.5, 4.3.	7, and 4.3.8]				
\boxtimes	Rooftop areas	Dispe	erse rooftop runoff (SD-B)			runoff roofs capture r		re runoff al; SD-E)		
		Full	Partial	Full	Partial	Full	Partial			
							<u> </u>			
	Landscaped areas	Use water-efficient landscaping (SD-J) Install efficient irrigation system (SD-K)		n systems D-K)	(SD-L)					
		Full	Partial	Full	Partial	Full	Partial			
	Water features (pools, spas, etc.)	designated washing		Drain feature to the sanitary sewer (if allowed) (SC-B)		Drain feature to a pervious area (SC-C)				
		Full	Partial	Full	Partial	Full	Partial			
		\boxtimes								

Note: Justification is required in Table 4 for any feature not selecting at least one BMP (either full or partial implementation). For Group 2 features this means not selecting either SD-B or SD-D. Additional justifications may be required on request by County staff. Also use Table 4 to describe sources or BMPs other than those listed.

Template Date: December 11, 2018 Preparation Date: February 7, 2020

Table 3 -Baseline BMPs for Pollutant-generating Sources (Group 4)

A. Requirements for Documentation Select either or both as applicable.	Completion of Part B is <u>not</u> required because: ☐ This is a Small Residential Project, OR ☐ None of these sources or features is proposed.			E.1-1 (Sinclude	⊠ Source Control BMP Requirements Worksheet E.1-1 (SC in Appendix E of the BMP Design Manual) is included as Attachment 3 (optional unless requested by County staff).				
B. Sources and BMPs	SC-B	SC-C	SC-D	SC-E	SC-F	SC-G	SC-H		
Select all proposed sources and features below. Then select the BMPs on the right to be implemented for each.	Plumb to sanitary sewer	Drain feature to a pervious area	Provide containment for spills and discharges	Prevent contact with rainfall	Isolate flows from adjacent areas	Prevent wind dispersal	Label with stencils or signs		
Common Source Areas									
☑ Trash & Refuse Storage			×	×	×	⋈			
☐ Materials & Equipment Storage									
☐ Loading & Unloading									
\square Fueling									
☐ Maintenance & Repair									
☐ Vehicle & Equipment Cleaning									
\square Food Preparation or Service									
<u>Distributed Features</u>									
☑ Storm drain inlets & catch basins							\boxtimes		
\square Interior floor drains and sumps									
☑ Drain lines (air conditioning, etc.)		⊠							
	×								

Provide the following in Table 4: (1) justification of any source area or feature with NO BMPs selected, (2) justification of individual unselected BMPs *if* requested by County staff, and (3) identification of any proposed pollutant-generating sources and BMPs not listed here.

Note: Pollutant-generating sources and features may <u>not</u> discharge directly to the MS4. Discharging to any of the stormwater BMPs identified in Table 5 Part B is also discouraged. If doing so, however, the source or feature area must be included in applicable DCV calculations.

Page | 4

Template Date: December 11, 2018

Table 4 - Explanations and Justifications for Table 2 and 3 Baseline BMPs

\square Check here if no explanations or justifications for Table 2 or 3 BMPs are required.

- **Required Justifications**: If NO BMPs are selected for a source or feature, justify why <u>all</u> BMPs are either not applicable or are infeasible. For Group 2 features NO BMPs means not selecting either SD-B or SD-D.
- If Requested: Justify why individual BMPs will not be implemented or will only be partially implemented.
- Additional Explanation: Describe any proposed features and/or BMPs not listed in Tables 2 or 3.

BMP-Fe Combin		Explanation						
Feature	Sidewalks, Walkways	Impervious area dispersion critera are not feasible for encorporation into this site design due to overland flow length restrictions on the siteplan, in additionto the						
BMP	Impervious area Dispersion	high impervious: pervious ratio of roof to adjacent landscape area.						
Feature	Patios, decks and courtyards	Impervious area dispersion critera are not feasible for encorporation into this site design due to overland flow length restrictions on the siteplan, in additionto the						
BMP	Impervious area dispersion	high impervious: pervious ratio of patio/pool deck to adjacent landscape area.						
Feature	Roof Areas	Impervious area dispersion critera are not feasible for encorporation into this si design due to overland flow length restrictions on the siteplan, in additionto the						
ВМР	Impervious area dispersion	high impervious: pervious ratio of roof to adjacent landscape area.						
Feature	Feature	Explanation						
BMP	ВМР							
Feature	Feature	Explanation						
BMP	ВМР							
Feature	Feature	Explanation						
BMP	ВМР							
Feature	Feature	Explanation						
BMP	BMP							

Template Date: December 11, 2018 Preparation Date: February 7, 2020

Table 5: DMA Structural Compliance Strategies and Documentation Part A – Selection and Application Structural Performance Standards 1. Selection of Standards (select one; see BMPDM Section 6.1) ☐ a. Pollutant control + hydromodification ☑ b. Pollutant control only (project is exempt from hydromodification requirements) 2. Application of Structural Performance Standards (select one; see BMPDM Section 1.7) New Development Projects: Standards apply to all impervious surfaces. ☐ **Redevelopment Projects:** Complete the calculations below. Select the applicable scenario based on the results. a. Existing impervious area (ft²) b. Impervious area created / replaced (ft²) c. % Impervious created / replaced [(b/a)*100] ☐ Scenario 1: c is 50% or more: Performance standards apply to all impervious surfaces (a + b). ☐ Scenario 2: c is less than 50%: Performance standards apply only to created or replaced impervious surfaces (b only). Part B – Compliance Strategies and Required Attachments Att. 1 Att. 2 Att. 3 Att. 4 Att. 5 **1.**Complete and submit each of the DMA Exhibits and Source Control BMP Previous SWOMP Storm Water Intake Existing Site and applicable attachments on the right. Construction Plan Worksheet Submittals Drainage Description Form Sheets (see Page 3) (see Page 1) X $|\mathsf{X}|$ \boxtimes X Att. 6 Att. 7 Att. 8 Att. 9 Att. 10 Att. 11 Att. 12 2. Indicate each compliance strategy below that will be DMAs w/ Critical used for one or more DMAs on the site. Structural DMAs w/ Coarse **DMAs** Pollutant Structural Installation without Sediment Maintenance Alternative Structural Control Hydromod. Yield Verification Compliance Agreements/ **Projects BMPs BMPs BMPs** Areas Form Plans ☐ Self-mitigating DMAs (BMPDM Section 5.2.1) \Box П П ☐ De Minimis DMAs (BMPDM Section 5.2.2) ☐ Self-retaining DMAs (BMPDM Section 5.2.3) Structural BMPs (select all that apply) ⊠Pollutant Control BMPs (BMPDM Section 5.4) \boxtimes \boxtimes \boxtimes \boxtimes П ☐ Hydromodification BMPs (BMPDM Chapter 6) Alternative Compliance Project (BMPDM Section 1.8) Please check this box after you complete this list. Corresponding attachments will be automatically selected on the right.

• Attachments 1, 2, and 5 are required for all projects.

Template Date: December 11, 2018 Preparation Date: February 7, 2020

Table 6: Critical Coarse Sediment Yield Area (CCSYA) Requirements

 Identify one applicable compliance pathway for the PDP below. Document your selection in Attachment 9.
A. Hydromodification Management Exemption (BMPDM Sections 1.6 and 6.1)
☑ PDP is Exempt from Hydromodification Management Requirements Select if hydromodification management exemption was selected in Table 4 Part A.1.
B. Watershed Management Area (WMAA) Mapping (BMPDM Appendix H.1.1.2)
□ WMAA mapping demonstrates the following: a. <5% of potential onsite CCYSAs will be impacted (built on or obstructed) b. All potential upstream offsite CCYSAs will be bypassed
C. Resource Protection Ordinance (RPO) Methods (BMPDM Appendix H.1.1.1)
C. Resource Protection Ordinance (RPO) Methods (BMPDM Appendix H.1.1.1) RPO Scenario 1: PDP is subject to and in compliance with RPO requirements a. Project requires one or more discretionary permits (RPO applicability is confirmed during discretionary review) b. Onsite AND upstream offsite CCSYAs will be avoided and/or bypassed RPO Scenario 2: PDP is entirely exempt/not subject to RPO requirements ² a. Project does not require discretionary permits b. Project will bypass all upstream offsite CCSYAs (no requirements for onsite CCSYAs)
□ RPO Scenario 1: PDP is subject to and in compliance with RPO requirements a. Project requires one or more discretionary permits (RPO applicability is confirmed during discretionary review) b. Onsite AND upstream offsite CCSYAs will be avoided and/or bypassed □ RPO Scenario 2: PDP is entirely exempt/not subject to RPO requirements² a. Project does not require discretionary permits

Template Date: December 11, 2018 Preparation Date: February 7, 2020

² Does not include PDPs utilizing exemption(s) via RPO Section 86.604(e)(2)(cc) or 86.604(e)(3).

Table 7 - Minimum Construction Stormwater RMPs

Table 7 – Minimum Construction Stormwater BMPs Minimum Required BMPs by Activity Type References					
Select all applicable activities and at least one BMP for each		County of San			
	Caltrans ³	Diego			
Erosion Control for Disturbed Slopes (choose at least 1 per seas					
☐ Vegetation Stabilization Planting ⁴ (Summer)	SS-2, SS-4				
☐ Hydraulic Stabilization Hydroseeding ⁹ (Summer)	SS-4				
☐ Bonded Fiber Matrix or Stabilized Fiber Matrix ⁵ (Winter)	SS-3				
☐ Physical Stabilization Erosion Control Blanket ⁷ (Winter)	SS-7				
☐ Erosion control for disturbed flat areas (slope < 5%)		:			
☑ County Standard Lot Perimeter Protection Detail	SC-2	PDS 659 ⁶			
☐ Use of Item A erosion control measures on flat areas	SS-3, SS-4, SS-7				
☐ County Standard Desilting Basin (must treat all site runoff)	SC-2	PDS 660 ⁷			
☐ Mulch, straw, wood chips, soil application	SS-6, SS-8				
\square Energy dissipation (required to control velocity for concent	rated runoff or dewa	atering discharge)			
☐ Energy Dissipater Outlet Protection	SS-10	RSD D-408			
☑ Sediment control for all disturbed areas					
☑ Silt Fence	SC-1				
☐ Fiber Rolls (Straw Wattles)	SC-5				
☑ Gravel & Sand Bags	SC-6, SC-8				
☐ Dewatering Filtration	NS-2				
☑ Storm Drain Inlet Protection	SC-10				
☐ Engineered Desilting Basin (sized for 10-year flow)	SC-2				
☑ Preventing offsite tracking of sediment					
☑ Stabilized Construction Entrance	TC-1				
☐ Construction Road Stabilization	TC-2				
☐ Entrance/Exit Tire Wash	TC-3				
☐ Entrance/Exit Inspection & Cleaning Facility	TC-1				
☐ Street Sweeping and Vacuuming	SC-7				
☐ Materials Management					
☑ Material Delivery & Storage	WM-1				
☑ Spill Prevention and Control	WM-4				
⊠ Waste Management ⁹					
☑ Waste Management Concrete Waste Management	WM-8				
☑ Solid Waste Management	WM-5				
☐ Sanitary Waste Management	WM-9				
☐ Hazardous Waste Management	WM-6				

³ See Caltrans 2017 Storm Water Quality Handbooks, Construction Site BMP Manual, available at: (http://www.dot.ca.gov/hq/construc/stormwater/manuals.htm)

⁴ Planting or Hydroseeding may be installed between May 1st and August 15th. Slope irrigation must be in place and operable for slopes >3 feet. Vegetation must be watered and established prior to October 1st. A contingency physical BMP must be implemented by August 15th if vegetation is not established by that date. If landscaping is proposed, erosion control measures must also be used while landscaping is being established. Established vegetation must have a subsurface mat of intertwined mature roots with a uniform vegetative coverage of 70 percent of the natural vegetative coverage or more on all disturbed areas.

⁵ All slopes over three feet must have established vegetative cover prior to final permit approval.

⁶ County PDS 659. Standard Lot Perimeter Protection Design System (Bldg. Division)

⁷ County PDS 660. County Standard Desilting Basin for Disturbed Areas of 1 Acre or Less Bldg. Division

⁸ Regional Standard Drawing D-40 – Rip Rap Energy Dissipater (also acceptable for velocity reduction)
⁹ Applicants are responsible to apply appropriate BMPs for specific wastes (e.g., BMP WM-8 for concrete).

Table 8 - Explanations and Justifications for Construction Phase BMPs

☑ Check here if no explanations or justifications for Table 7 BMPs are required.

Justifications for Table 7 Temporary Construction Phase BMPs

- **Required Justifications**: Justify all construction activity types for which NO BMPs were selected.
- If Requested: Justify why specific individual BMPs were not selected.
- **Additional Explanation**: Describe any proposed features and/or BMPs not listed in Table 7.

Activity	Type / BMP	Explanation
Activity Type	Activity Type	Explanation
BMP	BMP	
Activity Type	Activity Type	Explanation
BMP	BMP	
Activity Type	Activity Type	Explanation
BMP	BMP	
Activity Type	Activity Type	Explanation
BMP	BMP	
Activity Type	Activity Type	Explanation
BMP	BMP	
Activity Type	Activity Type	Explanation
BMP	BMP	
Activity Type	Activity Type	Explanation
BMP	BMP	

Template Date: December 11, 2018 Preparation Date: February 7, 2020 Page | 9



This form establishes Stormwater Quality Management Plan (SWQMP) requirements for Development Projects per Sections 67.809 and 67.811 of the County of San Diego Watershed Protection Ordinance (WPO). See **Storm Water Intake Form Instructions** for additional guidance and explanation of terms.

	Part 1. Project Information					
Project Name:	Carefield Senior Care Facility, Bonsall					
Record ID (Permit) No(s):	Record ID (Permit) No(s): PDS2019-STP-19-005, PDS2019-REZ-19-001					
Assessor's Parcel No(s):	: 126-230-55-00					
Street Address (or Intersection):	Mission Rd. & Thoroughbred Lane, Bonsall, California					
City, State, Zip:	Bonsall, CA 92003					
Part 2. Applicant / Project	Proponent Information					
Name:	Steven Barklis					
Company:	Carefield Senior Living					
Street Address:	201 Lomas Santa Fe Drive, Ste 450					
City, State, Zip:	Solana Beach, CA 92075					
Phone Number	858-259-5591					
Email:	svbark@aol.com					
I have reviewed the information in this form and it is true and correct to the best of my knowledge.						
Applicant / Project Proponent Sign	lature: Signature Stem W. Ben Date: Date 2/7/2020					
Part 3. Exemption from Classification as a Development Project (Check any that apply)						
Stormwater management measures apply to your project only if it meets the definition of a Development Project per County of San Diego BMP Design Manual Section 1.3 (Defining a Project). Your project is exempt						
from permanent post-construction stormwater management requirements if any of following apply:						
from permanent post-construction	stormwater management requirements if any of following apply:					
\square a. It includes only temporary ac	tivity that will not result in permanent post-construction changes.					
□ a. It includes only temporary ac□ b. It does not consist of constru	tivity that will not result in permanent post-construction changes. ction, rehabilitation, redevelopment, and/or reconstruction work.					
□ a. It includes only temporary ac□ b. It does not consist of constru	tivity that will not result in permanent post-construction changes.					
 □ a. It includes only temporary ac □ b. It does not consist of constru □ c. It includes only replacement 	tivity that will not result in permanent post-construction changes. ction, rehabilitation, redevelopment, and/or reconstruction work.					
 □ a. It includes only temporary ac □ b. It does not consist of constru □ c. It includes only replacement □ d. It includes only repair or imp 	tivity that will not result in permanent post-construction changes. ction, rehabilitation, redevelopment, and/or reconstruction work. of impervious surfaces that are part of a routine maintenance activity. rovements to an existing building or structure that do not alter the size. annuade source of pollutants to stormwater, and (2) does not reduce the					
 □ a. It includes only temporary ac □ b. It does not consist of constru □ c. It includes only replacement □ d. It includes only repair or imp □ e. It (1) does not contribute a m natural absorption and infilt 	tivity that will not result in permanent post-construction changes. etion, rehabilitation, redevelopment, and/or reconstruction work. of impervious surfaces that are part of a routine maintenance activity. rovements to an existing building or structure that do not alter the size. annuade source of pollutants to stormwater, and (2) does not reduce the ration abilities of the land.					
□ a. It includes only temporary ac □ b. It does not consist of constru □ c. It includes only replacement □ d. It includes only repair or imp □ e. It (1) does not contribute a m natural absorption and infilt	tivity that will not result in permanent post-construction changes. etion, rehabilitation, redevelopment, and/or reconstruction work. of impervious surfaces that are part of a routine maintenance activity. rovements to an existing building or structure that do not alter the size. annuade source of pollutants to stormwater, and (2) does not reduce the ration abilities of the land. ked - CONTINUE to Part 4.					
□ a. It includes only temporary ac □ b. It does not consist of constru □ c. It includes only replacement □ d. It includes only repair or imp □ e. It (1) does not contribute a m natural absorption and infilt: If NONE of the Boxes are checked If ANY of the Boxes are checked	tivity that will not result in permanent post-construction changes. etion, rehabilitation, redevelopment, and/or reconstruction work. of impervious surfaces that are part of a routine maintenance activity. rovements to an existing building or structure that do not alter the size. annuade source of pollutants to stormwater, and (2) does not reduce the ration abilities of the land.					
□ a. It includes only temporary ac □ b. It does not consist of constru □ c. It includes only replacement of the line of the l	tivity that will not result in permanent post-construction changes. ction, rehabilitation, redevelopment, and/or reconstruction work. of impervious surfaces that are part of a routine maintenance activity. rovements to an existing building or structure that do not alter the size. annuade source of pollutants to stormwater, and (2) does not reduce the ration abilities of the land. ked - CONTINUE to Part 4. cd - STOP, sign under Part 2 above, and submit only this page. Do not County staff, attach an explanation of the exemption(s) being claimed.					
□ a. It includes only temporary ac □ b. It does not consist of constru □ c. It includes only replacement □ d. It includes only repair or imp □ e. It (1) does not contribute a m natural absorption and infilt: If NONE of the Boxes are checked If ANY of the Boxes are checked	tivity that will not result in permanent post-construction changes. etion, rehabilitation, redevelopment, and/or reconstruction work. of impervious surfaces that are part of a routine maintenance activity. rovements to an existing building or structure that do not alter the size. anmade source of pollutants to stormwater, and (2) does not reduce the ration abilities of the land. ked - CONTINUE to Part 4. ed - STOP, sign under Part 2 above, and submit only this page. Do not county staff, attach an explanation of the exemption(s) being claimed.					
□ a. It includes only temporary ac □ b. It does not consist of constru □ c. It includes only replacement of the line of the l	tivity that will not result in permanent post-construction changes. ction, rehabilitation, redevelopment, and/or reconstruction work. of impervious surfaces that are part of a routine maintenance activity. rovements to an existing building or structure that do not alter the size. annuade source of pollutants to stormwater, and (2) does not reduce the ration abilities of the land. ked - CONTINUE to Part 4. cd - STOP, sign under Part 2 above, and submit only this page. Do not County staff, attach an explanation of the exemption(s) being claimed.					

Template Date: December 11, 2018

LUEG: SW Intake Form

Part 4. Required Information for All Development Projects						
A	1. Existing (pre-develop impervious surf	ment)	2. Created or replaced impervious surfaces (ft²)	3. Total disturbed area (acres or ft²)		
	0		98,671	189,409		
B	M Check here and	l provide a W	/DID# if this project is subject	WDID # (if issued)		
	to the Californi 2009-0009-DV		on General Permit (Order No.	TBD		
\sim	5. Priority Clas	sification	& Stormwater Quality M	lanagement Plan Form Selection		
(A)	If your project i	s the follou	ving (select one)	B You must complete		
☐ St	andard Project			→ Standard SWQMP Form		
	a. Project is East of	the Pacific/S	Salton Sea Divide			
	b. None of the PDF	criteria belo	w applies			
⊠ P₁	riority Developm	ent Project	t (PDP)	→ PDP SWQMP Form		
□ 1 ,	. Project is part of a	n existing PI	OP, <u>OR</u>			
\boxtimes 2	. Project does any o	of the following	ng:			
	_		f 10,000 ft² or more of			
	impervious surf					
L	□ b. Creates or replaces a combined total of 5,000 ft² or more of impervious surface within one or more of the following uses: (1) parking lots; (2) streets, roads, highways, freeways, and/or driveways; (3) restaurants; and (4) hillsides					
	 □ c. Creates or replaces a combined total of 5,000 ft² or more of impervious surface within one or more of the following uses: (1) automotive repair shops; and (2) retail gasoline outlets 					
	☐ d. Discharges directly to an Environmentally Sensitive Area (ESA) AND creates or replaces 2,500 ft² or more of impervious surface					
	\square e. Disturbs one or more acres of land (43,560 ft ²) and is expected to generate pollutants post-construction					
	☐ f. Is a <u>redevelopment</u> project that creates or replaces 5,000 ft² or more of impervious surface on a site already having at least 10,000 ft² of impervious surface					
☐ G	reen Streets PDF	Exemption	n²	→ Green Streets PDP Exemption SWQMP Form		
• If	 On completion of Parts 4 and 5, sign under Part 2 above and submit this form to the County. If requested, attach supporting documentation to justify selections made or exemptions claimed. If this is a PDP that is part of a larger existing PDP, you will be required to attach a copy of the existing SWQMP to the newer SWQMP submittal. 					

Template Date: December 11, 2018 LUEG: SW Intake Form

¹ Available at: https://www.waterboards.ca.gov/water-issues/programs/stormwater/construction.html
² *Green Streets PDP Exemption Projects* are those claiming exemption from PDP classification per WPO Section 67.811(b)(2) because they consist exclusively of *either* 1) development of new sidewalks, bike lanes, and/or trails; *or* 2) improvements to existing roads, sidewalks, bike lanes, and/or trails.

2.0 General Requirements

- Attachment 2 consolidates exhibits and plans required for the entire project.
- Complete the table below to indicate which sub-attachments are included with the submittal. Sub-attachments that are not applicable can be excluded from the submittal.
- Unless otherwise stated, features and BMPs identified and described in each corresponding Attachment (6 through 9) must be shown on applicable DMA Exhibits and construction plans submitted for the project.

Sub-attachments	Requirement		
☑ 2.1: DMA Exhibits	All PDPs		
☐ 2.2: Individual Structural BMP DMA Mapbook	PDPs with structural BMPs		
☑ 2.3: Construction Plan Sets	All projects		

PER DISCUSSION WITH STAFF, MAPBOOKS SHALL BE DEFERRED TO ENGINEERING.

County of San Diego SWQMP Attachment 2 Template Date: January 16, 2019 Page 2.0-1

Preparation Date: 2/22/2019

2.1 DMA Exhibits


- DMA Exhibits must show all DMAs on the project site. Exhibits must include all applicable features identified in applicable SWQMP attachments.
- Exhibits may be prepared individually for the BMPs associated with each applicable SWQMP Attachment (6, 7, 8, and/or 9) or combined into one or more consolidated exhibits.
- Use this checklist to ensure required information is included on each exhibit (copy as needed).

A. Features required for all exhibits						
up (A, B, C, D) ⊠ Topography and impervious areas						
water \Bigsiz Existing drainage network, directions,						
and offsite connections						
DMA) Information						
irections, and 🛛 DMA boundaries, ID numbers, areas,						
and type (structural BMP, de minimis,						
etc.)						
res, and BMPs						
ng □ Construction BMPs ²						
⋈ Baseline source control BMPs						
\square Baseline source control BMPs						
Specific to Individual SWQMP Attachments ³						
mpervious dispersion areas						
ree wells						
pollutant control BMPs						
nydromodification management BMPs						
Compliance (POC) for hydromodification management						
\square Proposed drainage boundary and drainage area to each POC						
YAs □ Bypass of onsite CCSYAs						
☐ Bypass of upstream offsite CCSYAs						

¹ Group 1-4 features and baseline BMPs from PDP SWQMP Tables 2 and 3.

² Minimum Construction Stormwater BMPs from PDP SWQMP Table 7.


³ Identify the location, ID numbers, type, and size/detail of BMPs.




NOTES:

- 1. SITE IS UNDERLAIN BY HYDROLOGIC SOIL GROUP TYPES A (EAST OF SOILS BOUNDARY) AND D (WEST OF SOILS BOUNDARY).
- 2. GROUNDWÂTER WAS NOT ENCOUNTERED IN 25 FOOT EXPLORATORY BORINGS.
- 3. NO EXISTING HYDROLOGIC FEATURES EXIST ONSITE.
- 4. REFER TO EROSION CONTROL PLAN FOR EROSION AND SEDIMENT CONTROL BMPS.
- 5. SD-B IMPLEMENTED AS APPLICABLE FOR DOWNSPOUT DISCONNECTION AND HARDSCAPE DISCONNECTION.
- 6. SD-D IMPLEMENTED VIA PERMEABLE PAVER THROUGHOUT PARKING AND DRIVE AISLES.
- 7. SC-B PLUMB FIRE SPRINKLER TEST SYSTEM TO SANITARY SEWER.
- 8. SC-C ROUTE AC DRAIN LINES TO A PERVIOUS AREA
- 9. SC-H STORMDRAIN INLET STENCIL
- 10. AREA DRAIN DESIGN WILL BE PROVIDED IN ENGINEERING, TO DRAIN DMA 1 TO THE APPROPRIATE BMP.
- 11. PERMEABLE PAVERS SHALL BE DESIGNED TO SAN DIEGO COUNTY SELF RETAINING STANDARDS.

PERMEABLE PAVER TYPICAL SECTION



DMA	IMPERVIOUS	PERVIOUS	TOTAL AREA
DMA -1	36,784	18,397	55,181
DMA -2	15,657	8,721	24,378
DMA -3	30,771	6,518	37,289
DMA -4	2,328	23,380	25,708
DMA -5	-	23,869	23,869
DMA -6	7,065	7,698	14,763
DMA - 7	6,066	2,155	8,221





CAREFIELD SENIOR CARE FACILITY BONSALL, CALIFORNIA

DRAINAGE MANANGEMENT EXHIBIT

2.2 Individual Structural BMP DMA Mapbook

- Use this page as a cover sheet for the Structural DMA Mapbook.
- An individual Structural DMA Mapbook must be submitted for any project site with one or more structural BMPs. One Mapbook is required for each unique subsequent owner with responsibility for maintenance of a Structural BMP. Mapbook exhibits will be incorporated as exhibits in Stormwater Maintenance Agreements (SWMAs) and Maintenance Notifications (MNs). See Attachment 11 for additional information on maintenance agreements. If the Mapbook has been provided for each subsequent owner in Attachment 11, they are not required here.
- Place each map on 8.5"x11" paper.
- Show at a minimum the DMA, Structural BMP, Assessor's parcel boundaries with parcel numbers, and any existing hydrologic features within the DMA.

	All Mapbooks are attached
\boxtimes	All Mapbooks are in Attachment 11

PER DISCUSSION WITH STAFF, MAPBOOKS SHALL BE DEFERRED TO ENGINEERING.

County of San Diego SWQMP Sub-attachment 2.2 (DMA Mapbook)

Template Date: January 16, 2019

Page 2.2-1

Preparation Date: 2/22/2019


2.3 Construction Plan Sets


- DMAs, features, and BMPs identified and described in this attachment must also be shown on all applicable construction and landscape plans.
- As applicable, plan sheets must identify:
 - o All features and BMPs identified in Sub-attachment 2.1 (DMA Exhibits).
 - The additional information listed below.
- Use this checklist to ensure required information is included on each plan (copy as needed).

Plan Type	Preliminary Grading Plan					
Required Information ⁴						
☐ Structural BMP(s) and Significant Site Design BMPs (if applicable) with ID numbers.						
_	ng and drainage design shown on the plans must be consistent with the delineation of wn on the DMA exhibit.					
⊠ Details ar BMPs (if a	nd specifications for construction of Structural BMP(s) and Significant Site Design pplicable).					
☐ Signage in	dicating the location and boundary of structural BMP(s) as required by County staff.					
☐ How to ac	cess the structural BMP(s) to inspect and perform maintenance.					
or other fe	that are provided to facilitate inspection (e.g., observation ports, cleanouts, silt posts, eatures that allow the inspector to view necessary components of the structural BMP are to maintenance thresholds).					
reference identified	nce thresholds specific to the structural BMP(s), with a location-specific frame of (e.g., level of accumulated materials that triggers removal of the materials, to be based on viewing marks on silt posts or measured with a survey rod with respect to achmark within the BMP).					
☐ Recomme	nded equipment to perform maintenance.					
	olicable, necessary special training or certification requirements for inspection and accepersonnel such as confined space entry or hazardous waste management.					
	\square Include landscaping plan sheets (if available) showing vegetation requirements for vegetated structural BMP(s).					
☐ All BMPs n	nust be fully dimensioned on the plans.					
\square When proprietary BMPs are used, site-specific cross-section with outflow, inflow, and manufacturer model number must be provided. Photocopies of general brochures are not acceptable.						
☐ Include all	$\hfill\square$ Include all source control and site design measures described in the SWQMP.					
☐ Include all	\square Include all construction BMPs described in the SWQMP.					

County of San Diego SWQMP Sub-attachment 2.3 (Construction Plans) Page 2.3-1 Template Date: January 16, 2019 Preparation Date: 2/22/2019


⁴ For Building Permit Applications, refer to Form PDS 272, https://www.sandiegocounty.gov/content/dam/sdc/pds/docs/pds272.pdf







PROPOSED CONSTRUCTION DETAILS FOR


CAREFIELD SENIOR CARE FACILITY, BONSALL, CALIFORNIA













NOTE: SEE DMA EXHIBIT FOR TYPICAL PAVER DETAIL

SHEET C-700




01312020 SITE PLAN REZONE APPLICATION




NOTES:

- 1. SITE IS UNDERLAIN BY HYDROLOGIC SOIL GROUP TYPES A (EAST OF SOILS BOUNDARY) AND D (WEST OF SOILS BOUNDARY).
- 2. GROUNDWÂTER WAS NOT ENCOUNTERED IN 25 FOOT EXPLORATORY BORINGS.
- 3. NO EXISTING HYDROLOGIC FEATURES EXIST ONSITE.
- 4. REFER TO EROSION CONTROL PLAN FOR EROSION AND SEDIMENT CONTROL BMPS.
- 5. SD-B IMPLEMENTED AS APPLICABLE FOR DOWNSPOUT DISCONNECTION AND HARDSCAPE DISCONNECTION.
- 6. SD-D IMPLEMENTED VIA PERMEABLE PAVER THROUGHOUT PARKING AND DRIVE AISLES.
- 7. SC-B PLUMB FIRE SPRINKLER TEST SYSTEM TO SANITARY SEWER.
- 8. SC-C ROUTE AC DRAIN LINES TO A PERVIOUS AREA
- 9. SC-H STORMDRAIN INLET STENCIL
- 10. AREA DRAIN DESIGN WILL BE PROVIDED IN ENGINEERING, TO DRAIN DMA 1 TO THE APPROPRIATE BMP.
- 11. PERMEABLE PAVERS SHALL BE DESIGNED TO SAN DIEGO COUNTY SELF RETAINING STANDARDS.

PERMEABLE PAVER TYPICAL SECTION




DMA	IMPERVIOUS	PERVIOUS	TOTAL AREA
DMA -1	36,784	18,397	55,181
DMA -2	15,657	8,721	24,378
DMA -3	30,771	6,518	37,289
DMA -4	2,328	23,380	25,708
DMA -5	-	23,869	23,869
DMA -6	7,065	7,698	14,763
DMA - 7	6,066	2,155	8,221





CAREFIELD SENIOR CARE FACILITY BONSALL, CALIFORNIA

DRAINAGE MANANGEMENT EXHIBIT



3.0 Cover Sheet and General Requirements

- Standard SWQMP Form Table 2 and PDP SWQMP Form Table 3 require the identification of pollutant-generating sources and associated BMPs for development projects.
- In some cases, County staff may request additional, more detailed documentation of source control BMP design details. If requested, applicants must submit a completed copy of this Source Control BMP Worksheet. This requirement can be satisfied either by submitting a copy of BMPDM Attachment E.1 (Source Control BMP Requirements) or equivalent documentation at the County's discretion.
- Submit this documentation using this cover sheet.
- Sources and BMPs must also be shown as applicable on DMA exhibits and construction plans (see Attachment 2).

County of San Diego SWQMP Attachment 3 (Source Control BMP Cover Sheet) Page 3.0-1 Template Date: December 28, 2018 Preparation Date: 2/25/2019

E.2 Source Control BMP Requirements

Worksheet E.1-1: Source Control BMP Requirements

How to comply: Projects must comply with this requirement by implementing all source control BMPs listed in this section that are applicable and feasible for their project. Applicability must be determined through consideration of the development project's features and anticipated pollutant sources. Appendix E.2 provides guidance for identifying source control BMPs applicable to a project. The Standard and PDP SWQMP templates include sections that must be used to document compliance with source control BMP requirements.

How to use this worksheet:

- 1. Review Column 1 and identify which of these potential sources of storm water pollutants apply to your site. Check each box that applies.
- 2. Review Column 2 and incorporate all of the corresponding applicable BMPs in your project site plan.
- 3. Review Columns 3 and 4 and incorporate all of the corresponding applicable permanent controls and operational BMPs in a table in your project-specific storm water management report. Describe your specific BMPs in an accompanying narrative, and explain any special conditions or situations that required omitting BMPs or substituting alternatives.

If These Sources Will Be on the Project Site	Then Your SWQMP Must Consider These Source Control BMPs					
1 Potential Sources of Runoff Pollutants	2 Permanent Controls—Show on Drawings	3 Permanent Controls—List in Table and Narrative	4 Operational BMPs—Include in Table and Narrative			
X A. Onsite storm drain inlets □ Not Applicable	X Locations of inlets.	Mark all inlets with the words "No Dumping! Flows to Bay" or similar. See stencil template provided in Appendix I-4	 X Maintain and periodically repaint or replace inlet markings. X Provide storm water pollution prevention information to new site owners, lessees, or operators. X See applicable operational BMPs in Fact Sheet SC-44, "Drainage System Maintenance," in the CASQA Storm Water Quality Handbooks at https://www.casqa.org/resources/bmp-handbooks X Include the following in lease agreements: "Tenant shall not allow anyone to discharge anything to storm drains or to store or deposit materials so as to create a potential discharge to storm drains." 			

If These Sources Will Be on the Project Site		Then Your SWQMP must consider These Source Control BMPs					
	1 Potential Sources of	2 Permanent Controls—Show on	P	3 ermanent Controls—List in Table		4 Operational BMPs—Include in	
	Runoff Pollutants	Drawings		and Narrative		Table and Narrative	
	B. Interior floor drains and elevator shaft sump pumps			State that interior floor drains and elevator shaft sump pumps will be plumbed to sanitary sewer.		Inspect and maintain drains to prevent blockages and overflow.	
X	Not Applicable						
X	C. Interior parking garages Not Applicable			State that parking garage floor drains will be plumbed to the sanitary sewer.		Inspect and maintain drains to prevent blockages and overflow.	
X	D1. Need for future indoor & structural pest control Not Applicable		X	Note building design features that discourage entry of pests.	X	Provide Integrated Pest Management information to owners, lessees, and operators.	

If These Sources Will Be on the Project Site	Then Y	our SWQMP must consider These So	urce Control BMPs
1 Potential Sources of Runoff Pollutants	2 Permanent Controls—Show on Drawings	3 Permanent Controls—List in Table and Narrative	4 Operational BMPs—Include in Table and Narrative
X D2. Landscape/ Outdoor Pesticide Use ☐ Not Applicable	 □ Show locations of existing trees or areas of shrubs and ground cover to be undisturbed and retained. □ Show self-retaining landscape areas, if any. X Show storm water treatment facilities. 	State that final landscape plans will accomplish all of the following. Preserve existing drought tolerant trees, shrubs, and ground cover to the maximum extent possible. X Design landscaping to minimize irrigation and runoff, to promote surface infiltration where appropriate, and to minimize the use of fertilizers and pesticides that can contribute to storm water pollution. X Where landscaped areas are used to retain or detain storm water, specify plants that are tolerant of periodic saturated soil conditions. Consider using pest-resistant plants, especially adjacent to hardscape. X To ensure successful establishment, select plants appropriate to site soils, slopes, climate, sun, wind, rain, land use,	 X Maintain landscaping using minimum or no pesticides. X See applicable operational BMPs in Fact Sheet SC-41, "Building and Grounds Maintenance," in the CASQA Storm Water Quality Handbooks at https://www.casqa.org/resources/bmp-handbooks X Provide IPM information to new owners, lessees and operators.

I	f These Sources Will Be on the Project Site	Then Your SWQMP must consider These Source Con				ontrol BMPs		
	1 Potential Sources of Runoff Pollutants		Permanent Controls—Show on Drawings Permanent Controls—List in Table and Narrative			4 Operational BMPs—Include in Table and Narrative		
X	decorative fountains, and other water features.	X	Show location of water feature and a sanitary sewer cleanout in an accessible area within 10 feet.	X	If the local municipality requires pools to be plumbed to the sanitary sewer, place a note on the plans and state in the narrative that this connection will be made according to local requirements.	X	See applicable operational BMPs in Fact Sheet SC-72, "Fountain and Pool Maintenance," in the CASQA Storm Water Quality Handbooks at https://www.casqa.org/resources/bmp-handbooks	
X			For restaurants, grocery stores, and other food service operations, show location (indoors or in a covered area outdoors) of a floor sink or other area for cleaning floor mats, containers, and equipment. On the drawing, show a note that this drain will be connected to a grease interceptor before discharging to the sanitary sewer.	0 0	the designated cleaning area.			

If These Sources Will Be on the Project Site 	Then Your SWQMP must consider These Source Control BMPs					
Potential Sources of	2 Permanent Controls—Show on Drawings	3 Permanent Controls—List in Table and Narrative	4 Operational BMPs—Include in Table and Narrative			
X G. Refuse areas □ Not Applicable	X Show where site refuse and recycled materials will be handled and stored for pickup. See local municipal requirements for sizes and other details of refuse areas. X If dumpsters or other receptacles are outdoors, show how the designated area will be covered, graded, and paved to prevent runon and show locations of berms to prevent runoff from the area. Also show how the designated area will be protected from wind dispersal. Any drains from dumpsters, compactors, and tallow bin areas must be connected to a grease removal device before discharge to sanitary sewer.	 X State how site refuse will be handled and provide supporting detail to what is shown on plans. X State that signs will be posted on or near dumpsters with the words "Do not dump hazardous materials here" or similar. 	Provide adequate number of receptacles. Inspect receptacles regularly; repair or replace leaky receptacles. Keep receptacles covered. Prohibit/prevent dumping of liquid or hazardous wastes. Post "no hazardous materials" signs. Inspect and pick up litter daily and clean up spills immediately. Keep spill control materials available on- site. See Fact Sheet SC-34, "Waste Handling and Disposal" in the CASQA Storm Water Quality Handbooks at https://www.casqa.org/resources/bmp-handbooks			

	These Sources Will Be on the Project Site	Then Your SWQMP must consider These Source Control BMPs				l BMPs		
	1 Potential Sources of Runoff Pollutants			P	Permanent Controls—List in Table and Narrative		4 Operational BMPs—Include in Table and Narrative Table and Narrative	
	H. Industrial processes. Not Applicable		Show process area.		If industrial processes are to be located onsite, state: "All process activities to be performed indoors. No processes to drain to exterior or to storm drain system."		See Fact Sheet SC-10, "Non- Storm Water Discharges" in the CASQA Storm Water Quality Handbooks at https://www.casqa.org/resou rces/bmp-handbooks	
X	equipment or materials. (See rows J and K for source control measures for vehicle cleaning, repair, and maintenance.)		Show any outdoor storage areas, including how materials will be covered. Show how areas will be graded and bermed to prevent run-on or runoff from area and protected from wind dispersal. Storage of non-hazardous liquids must be covered by a roof and/or drain to the sanitary sewer system, and be contained by berms, dikes, liners, or vaults. Storage of hazardous materials and wastes must be in compliance with the local hazardous materials ordinance and a Hazardous Materials Management Plan for the site.		 Include a detailed description of materials to be stored, storage areas, and structural features to prevent pollutants from entering storm drains. Where appropriate, reference documentation of compliance with the requirements of local Hazardous Materials Programs for: Hazardous Waste Generation Hazardous Materials Release Response and Inventory California Accidental Release Prevention Program Aboveground Storage Tank Uniform Fire Code Article 80 Section 103(b) & (c) 1991 Underground Storage Tank Underground Storage Tank 		<u> </u>	

If These Sources Will Be on the Project Site	Then Your SWQM	P must consider These Source Control BMPs			
1 Potential Sources of Runoff Pollutants	2 Permanent Controls—Show on Drawings	3 Permanent Controls—List in Table and Narrative	4 Operational BMPs—Include in Table and Narrative		
□ J. Vehicle and Equipment Cleaning X Not Applicable	(1) Commercial/industrial facilities having vehicle / equipment cleaning needs must either provide a covered, bermed area for washing activities or discourage vehicle / equipment washing by removing hose bibs and installing signs prohibiting such uses. (2) Multi-dwelling complexes must have a paved, bermed, and covered car wash area (unless car washing is prohibited onsite and hoses are provided with an automatic shut- off to discourage such use). (3) Washing areas for cars, vehicles, and equipment must be paved, designed to prevent run-on to or runoff from the area, and plumbed to drain to the sanitary sewer. (4) Commercial car wash facilities must be designed such that no runoff from the facility is discharged to the storm drain system. Wastewater from the facility must discharge to the sanitary sewer, or a wastewater reclamation system must be installed.	If a car wash area is not provided, describe measures taken to discourage onsite car washing and explain how these will be enforced.	Describe operational measures to implement the following (if applicable): Washwater from vehicle and equipment washing operations must not be discharged to the storm drain system. Car dealerships and similar may rinse cars with water only. See Fact Sheet SC-21, "Vehicle and Equipment Cleaning," in the CASQA Storm Water Quality Handbooks at https://www.casqa.org/resou rces/bmp-handbooks		

If These Sources Will Be on the Project Site			Then Your SWQMP must consider These Source Control BMPs					
1 Potential S Runoff Po		-	2 Permanent Controls—Show on Drawings	P	3 ermanent Controls—List in Table and Narrative		4 Operational BMPs—Include in Table and Narrative	
□ K. Vehicle/E Repair Maintenar X Not Applica	and		Accommodate all vehicle equipment repair and maintenance indoors. Or designate an outdoor work area and design the area to protect from rainfall, run-on runoff, and wind dispersal. Show secondary containment for exterior work areas where motor oil, brake fluid, gasoline, diesel fuel, radiator fluid, acid-containing batteries or other hazardous materials or hazardous wastes are used or stored. Drains must not be installed within the secondary containment areas. Add a note on the plans that states either (1) there are no floor drains, or (2) floor drains are connected to wastewater pretreatment systems prior to discharge to the sanitary sewer and an industrial waste discharge permit will be obtained.		State that no vehicle repair or maintenance will be done outdoors, or else describe the required features of the outdoor work area. State that there are no floor drains or if there are floor drains, note the agency from which an industrial waste discharge permit will be obtained and that the design meets that agency's requirements. State that there are no tanks, containers or sinks to be used for parts cleaning or rinsing or, if there are, note the agency from which an industrial waste discharge permit will be obtained and that the design meets that agency's requirements.	res	the report, note that all of the following trictions apply to use the site: No person must dispose of, nor permit the disposal, directly or indirectly of vehicle fluids, hazardous materials, or rinsewater from parts cleaning into storm drains. No vehicle fluid removal must be performed outside a building, nor on asphalt or ground surfaces, whether inside or outside a building, except in such a manner as to ensure that any spilled fluid will be in an area of secondary containment. Leaking vehicle fluids must be contained or drained from the vehicle immediately. No person must leave unattended drip parts or other open containers containing vehicle fluid, unless such containers are in use or in an area of secondary containment.	


If These Sources Will Be on the Project Site	Then Your SWC	rce Control BMPs	
1 Potential Sources of Runoff Pollutants	2 Permanent Controls—Show on Drawings	3 Permanent Controls—List in Table and Narrative	4 Operational BMPs—Include in Table and Narrative
L. Fuel Dispensing Areas X Not Applicable	 □ Fueling areas² must have impermeable floors (i.e., portland cement concrete or equivalent smooth impervious surface) that are (1) graded at the minimum slope necessary to prevent ponding; and (2) separated from the rest of the site by a grade break that prevents run-on of storm water to the MEP. □ Fueling areas must be covered by a canopy that extends a minimum of ten feet in each direction from each pump. [Alternative: The fueling area must be covered and the cover's minimum dimensions must be equal to or greater than the area within the grade break or fuel dispensing area1.] The canopy [or cover] must not drain onto the fueling area. 		□ The property owner must dry sweep the fueling area routinely. □ See the Business Guide Sheet, "Automotive Service—Service Stations" in the CASQA Storm Water Quality Handbooks at https://www.casqa.org/resources/bmp-handbooks

² The fueling area must be defined as the area extending a minimum of 6.5 feet from the corner of each fuel dispenser or the length at which the hose and nozzle assembly may be operated plus a minimum of one foot, whichever is greater.

If These Sources Will Be on the Project Site	Then Your SWQMP must consider These Source Control BMPs				
1 Potential Sources of Runoff Pollutants	2 Permanent Controls—Show on Drawings	3 Permanent Controls—List in Table and Narrative	4 Operational BMPs—Include in Table and Narrative		
M. Loading Docks X Not Applicable	 □ Show a preliminary design for the loading dock area, including roofing and drainage. Loading docks must be covered and/or graded to minimize run-on to and runoff from the loading area. Roof downspouts must be positioned to direct storm water away from the loading area. Water from loading dock areas should be drained to the sanitary sewer where feasible. Direct connections to storm drains from depressed loading docks are prohibited. □ Loading dock areas draining directly to the sanitary sewer must be equipped with a spill control valve or equivalent device, which must be kept closed during periods of operation. □ Provide a roof overhang over the loading area or install door skirts (cowling) at each bay that enclose the end of the trailer. 		 □ Move loaded and unloaded items indoors as soon as possible. □ See Fact Sheet SC-30, "Outdoor Loading and Unloading," in the CASQA Storm Water Quality Handbooks at https://www.casqa.org/resources/bmphandbooks 		

If These Sources Will Be on the Project Site	′	Then Your SWQMP must consider These Source Co	er These Source Control BMPs			
1 Potential Sources of Runoff Pollutants	Permanent Controls— Show on Drawings	3 Permanent Controls—List in Table and Narrative	4 Operational BMPs—Include in Table and Narrative			
X N. Fire Sprinkler Test Water□ Not Applicable		X Provide a means to drain fire sprinkler test water to the sanitary sewer.	X See the note in Fact Sheet SC-41, "Building and Grounds Maintenance," in the CASQA Storm Water Quality Handbooks at https://www.casqa.org/resour ces/bmp-handbooks			
O. Miscellaneous Drain or Wash Water □ Boiler drain lines X Condensate drain lines X Rooftop equipment □ Drainage sumps IX Roofing, gutters, and trim □ Not Applicable		 Boiler drain lines must be directly or indirectly connected to the sanitary sewer system and may not discharge to the storm drain system. Condensate drain lines may discharge to landscaped areas if the flow is small enough that runoff will not occur. Condensate drain lines may not discharge to the storm drain system. Rooftop mounted equipment with potential to produce pollutants must be roofed and/or have secondary containment. Any drainage sumps onsite must feature a sediment sump to reduce the quantity of sediment in pumped water. Avoid roofing, gutters, and trim made of copper or other unprotected metals that may leach into runoff. 				

If These Sources Will Be on the Project Site	Then Your SWQMP must consider These Source Control BMPs							
1 Potential Sources of Runoff Pollutants	2 Permanent Controls—Show on Drawings	3 Permanent Controls—List in Table and Narrative	4 Operational BMPs—Include in Table and Narrative					
X P. Plazas, sidewalks, and parking lots.□ Not Applicable			X Plazas, sidewalks, and parking lots must be swept regularly to prevent the accumulation of litter and debris. Debris from pressure washing must be collected to prevent entry into the storm drain system. Washwater containing any cleaning agent or degreaser must be collected and discharged to the sanitary sewer and not discharged to a storm drain.					



4.0 Cover Sheet

• If this SWQMP implements any requirements of an earlier master SWQMP submittal, a copy of that previous submittal must be attached under cover of this sheet.

NOT APPLICABLE

5.0 General Requirements

- Each Priority Development Project (PDP) must provide a description of existing site conditions and proposed changes to them, including changes to topography and drainage.
- Has a **Drainage Report** has been prepared for the PDP?

⊠ Yes

- Review of the Drainage Report must be concurrent with the PDP SWQMP.
- o Include the summary page of the Drainage Report with this cover page, and provide the following information:

Title: Preliminary Drainage Study for Carefield Senior Care Fecility, Bonsall

Prepared By: Tory R Walker Engineering

Date: 2/22/2019

 Do not complete the rest of this attachment (also exclude these additional pages from your submittal). Additional documentation of site and drainage conditions is not required unless requested by County staff.

Page 5.0-1

Preparation Date: 2/22/2019

□ **No** -- Complete and submit the remainder of this attachment below.

6.0 General Requirements

• Use this attachment to document all proposed (1) self-mitigating, (2) de minimis, and (3) self-retaining DMAs. Indicate under "DMA Compliance Option" below which design options will be used to satisfy structural performance requirements for one or more DMA.

DMA Compliance Option	Required Sub-attachments	BMPDM Design Resources		
⊠ Self-mitigating	• Sub-attachment 6.1	• BMPDM Section 5.2.1		
☐ De minimis	• Sub-attachment 6.2	• BMPDM Section 5.2.2		
⊠ Self-retaining¹	• Sub-attachment 6.3	• BMPDM Section 5.2.3 (all options)		
SSD-BMP Type(s) ☐ Impervious Area Dispersion	• Sub-attachment 6.3.1	• Fact Sheet SD-B (Appendix E.8)		
⊠ Tree Wells	• Sub-attachment 6.3.2	• Fact Sheet SD-A (Appendix E.7)		

- Submit this cover page and all "Required Sub-attachments" listed for each selected DMA compliance option.
- See the BMPDM sections and appendices listed under "BMPDM Design Resources" for additional explanation of design requirements. Each constructed feature must <u>fully</u> satisfy the requirements described in these resources, and any other guidance identified by the County.
- <u>DMA Exhibits and Construction Plans</u>: DMAs, features, and BMPs identified and described in this attachment must be shown on DMA Exhibits and all applicable construction plans submitted for the project. See Attachment 2 for additional instruction on exhibits and plans.

¹ If "Self-retaining" is selected, also choose the types of Significant Site Design BMPs (SSD-BMPs) to be used. SSD-BMPs are Site Design BMPs that are sized and constructed to fully satisfy all applicable Structural Performance Standards for a DMA.

County of San Diego SWQMP Attachment 6.0 (Cover Sheet)

Template Date: January 3, 2019

Page 6.0-1

Preparation Date: 2/7/2020

6.1 Self-mitigating DMAs (complete this page once for ALL self-mitigating DMAs)

Self-mitigating DMAs consist of natural or landscaped areas that drain directly offsite or to the public storm drain system. These DMAs are excluded from DCV calculations.

• Provide the information requested below for each proposed self-mitigating DMA. Add rows or copy the table if additional entries are needed.

DMA #	a. DMA	Incidental Impervious Area				
	Area (ft²)	b. Size(ft²)	c. % (b/a*100)	Permit # and Sheet #		
5	23,869					
		-				
		-				
		-				

- "DMA #", "DMA Area", and "Permit # and Sheet #" are required for all DMAs listed.
- "Incidental Impervious Area" calculations are required only where applicable (see below).
- Each self-mitigating DMA must <u>fully</u> satisfy all design requirements and restrictions described in BMPDM Section 5.2.1 and any other guidance or instruction identified by the County. Check the boxes below to confirm that all required conditions are satisfied <u>for every DMA listed</u>.
 - ☑ Each DMA is hydraulically separate from other DMAs that contain permanent storm water pollutant control BMPs.

Natural and Landscaped Areas

- ☑ Each DMA consists solely of natural or landscaped areas, except for incidental impervious areas (see below).
- ☑ Each area drains directly offsite or to the public storm drain system.
- ☑ Soils are undisturbed native topsoil, or disturbed soils that have been amended and aerated to promote water retention characteristics equivalent to undisturbed native topsoil.
- ☑ Vegetation is native and/or non-native/non-invasive drought tolerant species that do not require regular application of fertilizers and pesticides.

<u>Incidental Impervious Areas (if applicable; see above)</u>

Minor impervious areas may be permitted within the DMA if they satisfy the following criteria:

- ☐ They are not hydraulically connected to other impervious areas (unless it is a storm water conveyance system such as a brow ditch).
- \square They comprise less than 5% of the total DMA. Calculate the % incidental impervious area in the table above (c= b/a). DMAs are <u>not</u> self-mitigating if this area is 5% or greater.

6.2 De Minimis DMAs (complete this page once for ALL de minimis DMAs)

De minimis DMAs consist of areas too small to be considered significant contributors of pollutants and not practicable to drain to a BMP. They are excluded from DCV calculations. Examples include driveway aprons connecting to existing streets, portions of sidewalks, retaining walls, and similar features at the external boundaries of a project.

• Provide the information requested below for each proposed de minimis DMA. Add rows or copy the table if additional entries are needed.

DMA #	DMA Area (ft²)	Permit # and Sheet #

- "DMA #", "DMA Area", and "Permit # and Sheet #" are required.
- Each de minimis DMA must <u>fully</u> satisfy all design requirements and restrictions described in BMPDM Section 5.2.2 and any other guidance or instruction identified by the County.
- Check the boxes below to confirm that each required condition is satisfied for ALL de minimis DMAs on the site. A DMA must satisfy ALL these conditions to be considered de minimis.

☐ Each DMA listed is less than 250 square feet.
☐ Except for projects where 2 percent of the total added or replaced impervious surface of the project is less than 250 square feet, a de minimis DMA of 250 square feet or less may be allowed.
☐ The sum of all de minimis DMAs is less than 2 percent of the total added or replaced impervious surface of the project (from Storm Water Intake Form Part 4.A.2).
☐ Topography and land ownership constraints make runoff capture technically infeasible.
\square The use of de minimis DMAs has been minimized through effective site design.
\square All de minimis areas abut the perimeter of the development site.
☐ De minimis DMAs are not adjacent or hydraulically connected to each other.

6.3 Self-retaining DMAs using Significant Site Design BMPs

Self-retaining DMAs use Site Design BMPs to fully-retain the entire DCV, at a minimum. Site Design BMPs that fully retain the DCV, at a minimum, therefore replacing the need for a Structural BMP (S-BMP), are classified as Significant Site Design BMPs (SSD-BMPs). To satisfy pollutant control requirements only, self-retaining means retention of the entire DCV. However, under some circumstances, a self-retaining DMA can also satisfy hydromodification management requirements by implementing BMPs that retain a greater volume of runoff.

• Provide the information requested below for each proposed self-retaining DMA. Add rows or copy the table if additional entries are needed.

		BMP Type (cho	ose one per DMA)			
		Dispersion				
DMA #	DMA Area	Area	Tree Wells			
	(ft ²)	(Att. 6.3.1)	(Att. 6.3.2)	Permit # and Sheet #		
4	25,708					

Copy and Paste table here for additional DMAs

- "DMA #", "DMA Area", and "Permit # and Sheet #" are required.
- Select one BMP Type per DMA. Provide detailed documentation for each DMA in Attachments 6.3.1 (Impervious Dispersion Areas) and/or 6.3.2 (Tree Wells) below.
- Each self-retaining DMA must <u>fully</u> satisfy all design requirements and restrictions described in BMPDM Section 5.2.3, applicable BMPDM Appendix E Fact Sheets, and any other guidance or instruction identified by the County.

County of San Diego SWQMP Sub-attachment 6.3.1 (Impervious Area Dispersion) Page 6.3.1-1 Template Date: January 3, 2019 Preparation Date: 2/7/2020

²Applicants wishing to utilize parameters less conservative than listed here must submit modeling to support their proposal. Consult your project manager for more information.

³Including the permeable pavement.

6.3.1 Self-retaining DMAs with Impervious Dispersion Areas

Impervious area dispersion (dispersion) refers to the practice of effectively disconnecting impervious areas from directly draining to the storm drain system by routing runoff from impervious areas such as rooftops (through downspout disconnection), walkways, and driveways onto the surface of adjacent pervious areas. The intent is to slow runoff discharges and reduce volumes. Dispersion with partial or full infiltration results in significant volume reduction by means of infiltration and evapotranspiration. When adequately sized, dispersion can also be used to satisfy both the pollutant control and hydromodification management structural performance standards for a DMA.

- Each self-retaining DMA with impervious area dispersion must fully satisfy all design requirements and restrictions described in BMPDM Section 5.2.3, Fact Sheet SD-B: Impervious Area Dispersion, and any other guidance or instruction identified by the County.
- Documentation of compliance with all applicable conditions must be submitted with this subattachment using the *Summary Sheet for DMAs with Impervious Area Dispersion* on the next page. One version of this Summary Sheet must be completed for each applicable DMA.
- Applicants are responsible to comply with all other applicable requirements, regardless of whether they are included in the summary sheet.
- The following applies if the dispersion area is **native soil** (SD-B in Appendix E):
 - For pollutant control only, the DMA is considered self-retaining if the impervious to pervious ratio is:
 - 2:1 when the pervious area is composed of Hydrologic Soil Group A
 - 1:1 when the pervious area is composed of Hydrologic Soil Group B
- The following applies if the dispersion area includes amended soil (SD-B in Appendix E):
 - DMAs using impervious area dispersion can be considered to meet both pollutant control
 and hydromodification flow control requirements if the impervious to pervious area ratio is
 1:1 or less and all other design requirements of SD-B are satisfied, including 11 inches of
 amended soil.
- The following apply if the dispersion area is **permeable pavement** (SD-D in Appendix E):
 - For pollutant control only, a DMA is considered self-retaining if the ratio of total drainage area (including permeable pavement) to area of permeable pavement is 1.5:1 or less, and all other design requirements of SD-D are satisfied.
 - Hydromodification management performance standards can be satisfied using permeable pavement only if constructed to Structural BMP specifications. In this case, the permeable pavement must be sized and constructed in accordance with the requirements of INF-3.

UH€ 21--

²Applicants wishing to utilize parameters less conservative than listed here must submit modeling to support their proposal. Consult your project manager for more information.

³Including the permeable pavement.

Summary Sheet for DMAs with Impervious Area Dispersion (Complete 1 sheet per DMA)

DI	MA# 4								
A.	A. Minimum Sizing Requirements								
Ve	Verify that minimum standards are satisfied for the applicable dispersion area type below ² .								
Na	ative Soil (Pollutant Control	Only) Select one and provide calc	ulations below.						
	☐ <u>Soil Group A</u> : Ratio I:P is 2:1 or less ☐ <u>Soil Group B</u> : Ratio I:P is 1:1 or less								
	Impervious Area (ft²)	Permeable Dispersion Area (ft²)	Ratio I:P						
Ar	nended Soil (Pollutant Conti	ol plus Hydromodification Mar	nagement)						
Mι	ust satisfy both conditions and	provide calculations below.							
	☐ Ratio I:P is 1:1 or less, AND								
		of the pervious area consists of ar							
	Impervious Area (ft²)	Permeable Dispersion Area (ft²)	Ratio I:P						
Pe	ermeable Pavement (Polluta	nt Control Only) Provide calculat	tions below.						
\geq	Ratio DMA area to area of pe	rmeable pavement is 1.5:1 or less	i						
	DMA Area³ (ft²)	Permeable Pavement Area (ft²)	Ratio DMA:Pavement						
	25,708	23,380	1.1:1						
В.	Minimum Design Criteria								
Ch	neck the boxes below to confirm	n that each design criterion has b	een satisfied for the DMA.						
	Impervious Areas: ☑ Are graded to ensure area that the full DCV drains to the dispersion area before the runoff discharges from the DMA.								
Pe	ervious Dispersion Areas:								
	☐ Are less than 5% slope and sheet flow over a distance of at least 10 feet from inflow to overflow route.								
	☐ Have inflow velocities of 3 ft/s or less OR use energy dissipation methods (e.g., riprap, level spreader) for concentrated inflows.								
	spreader) for concentrated inflows.								
	•								
	☐ Are densely and robustly ver☐ Consist of soil types capable	nflows.	cies. to support vegetation (e.g., with						

Copy and Paste table here for additional DMAs

County of San Diego SWQMP Sub-attachment 6.3.1 (Impervious Area Dispersion) Page 6.3.1-3 Template Date: January 3, 2019 Preparation Date: 2/7/2020

 $^{^2}$ Applicants wishing to utilize parameters less conservative than listed here must submit modeling to support their proposal. Consult your project manager for more information.

³Including the permeable pavement.

6.3.2 Self-retaining DMAs with Tree Wells

Trees wells can provide a variety of benefits such as interception and increased infiltration of rainfall, reduced erosion, energy conservation, air quality improvement, and aesthetic enhancement. They can also be used to satisfy both pollutant control and hydromodification management performance standards for a DMA.

- Each self-retaining DMA with tree wells must fully satisfy all design requirements and restrictions described in BMPDM Section 5.2.3, Fact Sheet SD-A: Tree Wells, and any other guidance or instruction identified by the County.
- For pollutant control only, the DMA must retain the entire DCV. For hydromodification management, an additional volume must be retained in accordance with the sizing requirements presented in the DCV multiplier table in Fact Sheet SD-A.
- Documentation of compliance with applicable conditions must be submitted using the *Summary Sheet for Self-retaining DMAs with Tree Wells* on the next page. One version of this Summary Sheet must be completed for each applicable DMA.
- If both pollutant control and hydromodification standards apply, the soil depth of all tree wells in the DMA must be selected before determining the Required Retention Volume (RRV). Each tree well must be constructed to the selected depth. For pollutant control only, tree wells within a DMA may be constructed to different soil depths.
- In most cases tree wells must use Amended Soil per Fact Sheet SD-F. However, Structural Soil is required in some cases (e.g., placing the tree well next to a curb). See *Structural Requirements for Confined Tree Well Soil Volume* in Fact Sheet SD-A for additional explanation. If applicable, list the DMAs and Tree Well #s below for all tree wells requiring Structural Soil.

DMA#	Tree Wells Requiring Structural Soil (list Tree Well #s)
7	1, 2

The Design Capture Volume (DCV) must be known for each DMA in order to determine the
volume to be mitigated by the tree wells. Instructions for DCV calculation are provided in
BMPDM Appendix B.1. An automated version of Worksheet B.1 (Calculation of Design Capture
Volume) is available at www.sandiegocounty.gov/stormwater under the Development
Resources tab.

County of San Diego SWQMP Sub-attachment 6.3.2 (Tree Wells)

Template Date: January 3, 2019

Page 6.3.2-1

Preparation Date: 2/7/2020

Summary Sheet for Self-retaining DMAs with Tree Wells (complete one sheet per DMA)

DMA #: 7	MA #: 7 DMA Area (ft²): 8,221							
Required Retention Volume (RRV)								
a. Design Capture Volume (DCV; ft³):	331							
b. DCV Multiplier (Fact Sheet SD-A)								
Applicable Structural Performance Stan (select one)	ıdards	Tree we		Underlying soil type (A, B, C, or D)	DCV Multiplier			
\square Pollutant control only		An	y	All	1.0			
⊠ Pollutant control plus hydromodifi	cation	30)	A	1.6			
c. Required Retention Volume (ft³) []	DCV * D	CV Multipl	ier]		529			
Tree Well Credit Volume (add records	s or copy	y this shee	t as need	led for additional tree	wells)			
Provide the information below for each entry can be used for any group of tree					. A single			
Tree species or name TBD				No. tree wells	2			
Mature Canopy Diameter (ft) 25		Credi	t Volum	e per tree well (ft³)	290			
Tree well ID #(s) 1, 2 Combined Volume (ft³)								
Tree species or name				No. tree wells				
Mature Canopy Diameter (ft)		Credi		e per tree well (ft³)				
Tree well ID #(s)			Com	bined Volume (ft ³)				
Tree species or name				No. tree wells				
Mature Canopy Diameter (ft)		Credi	t Volum	e per tree well (ft ³)				
Tree well ID #(s)			Com	bined Volume (ft ³)				
Tree species or name				No. tree wells				
Mature Canopy Diameter (ft)		Credi	t Volum	e per tree well (ft³)				
Tree well ID #(s)			Com	bined Volume (ft³)				
Tree species or name				No. tree wells				
Mature Canopy Diameter (ft)		Credi	t Volum	e per tree well (ft³)				
Tree well ID #(s)			Com	bined Volume (ft³)				
Add the combined volumes above. Tota	al credit	volume m		Credit Volume (ft3) all or exceed the RRV.	280			

Copy and Paste table here for additional DMAs

7.0 General Requirements

- Submit this cover page and all required Sub-attachments for all structural BMPs proposed for the project.
- See the BMPDM sections and appendices listed under "BMPDM Design Resources" in the table below for additional explanation of design requirements. Constructed features must <u>fully</u> satisfy the requirements described in these resources, and any other guidance identified by the County.
- PDPs subject to hydromodification management requirements must also implement structural BMPs for flow control for hydromodification management. Completion of SWQMP Attachment 8 is also required for these BMPs.
- <u>DMA Exhibits and Construction Plans</u>: DMAs, features, and BMPs identified and described in this attachment must be shown on DMA Exhibits and all applicable construction plans submitted for the project. See Attachment 2 for additional instruction on exhibits and plans.
- <u>Structural BMP Certification</u>. All structural BMPs documented this attachment and in Attachment 8 must be certified by a registered engineer in Sub-attachment 7.1.
- <u>Structural BMP Verification</u>. Structural BMP installation must be verified by the County at the completion of construction. Applicants must complete an Installation Verification Form (Attachment 10).

Sub-attachments	Requirement	BMPDM Design Resources
(check all that are completed)		
☑ 7.1: Preparer's Certification	Required	• N/A
⊠ 7.2: Structural BMP Strategy	Required	 BMPDM Sections 5.1., 5.3, 5.4, and Chapter 6 BMPDM Appendix E (pages E-78 through E-
⊠ 7.3: Structural BMP Checklist(s)	Required	210)
□ 7.4: Identification and Narrative of Receiving Water and Pollutants of Concern	Required if flow-thru BMPs are proposed	• N/A
⊠ 7.5: Stormwater Pollutant Control Worksheet Calculations	Required	BMPDM Appendix B

County of San Diego SWQMP Attachment 7.0 (Cover Sheet) Template Date: January 3, 2019

Page 7.0-1
Preparation Date: 2/7/2020

${\bf 7.1\ Engineer\ of\ Work\ Certification\ for\ Structural\ BMPs}$

Date

Project Name	Carefield Senior Care Facility, Bonsall				
Permit Application Number					
	CERTIFICATION				
best management practices (BMI the design of the BMPs as defined design is consistent with the PDP is a design manual for compliand (Sections 67.801 et seq.) and reguan Diego Region Order No. Requirements for storm water mater m	ngineer in Responsible Charge of design of structural storm water Ps) for this project, and that I have exercised responsible charge over d in Section 6703 of the Business and Professions Code, and that the requirements of the County of San Diego BMP Design Manual, which ce with local County of San Diego Watershed Protection Ordinance gional MS4 Permit (California Regional Water Quality Control Board 9-2013-0001 as amended by R9-2015-0001 and R9-2015-0100 anagement. I have read and understand that the County of San Diego nents for managing urban runoff, including storm water, from land bed in the BMP Design Manual.				
the project being proposed and t impacts of this project's land dev that the plan check review of thi	as been completed to the best of my ability and accurately reflects the applicable BMPs proposed to minimize the potentially negative elopment activities on water quality. I understand and acknowledges PDP SWQMP by County staff is confined to a review and does not esponsible Charge of design of structural storm water BMPs for this r their design.				
=	ollutant control BMPs described in this attachment, this certification omodification Management BMPs described in Attachment 8 (check				
Joy R Walker					
Engineer of Work's Signature, P	'E Number & Expiration Date				
Tory R Walker, 45005 Exp . 3-3	1-2020				
Print Name					
Tory R Walker Engineering Company					
2/7/2020	Engineer's Seal:				
4///4040	Engineer 5 Sear.				

7.2.1 Narrative Strategy (Continue description on subsequent pages as necessary)

Describe the general strategy for structural BMP implementation at the project site. For pollutant control BMPs, your description must address the key points outlined in Section 5.1 of the BMP Design Manual, and the type of BMPs selected. For projects requiring hydromodification flow control BMPs, indicate whether pollutant control and flow control BMPs are integrated or separate.

The 36-hour demand for harvest and reuse is too low, so this option was not selected to meet treatment control requirements. The subject property is underlain by Mostly Hydrologic Soil Group Type D soils, and in order to create a buildable pad, will be graded flat, creating cut slopes on the northern side of the site, and fills on the southern portion. This creates a very low feasibility for structural infiltration BMP opportunities throughout the site, due mainly to the compaction and setback requirements for the proposed buildings, and partly due to the low infiltration capacity of the soils that are expected from the cut portions of the site. This is also supported by the AGS infiltration study results. Therefore, infiltration and partial retention BMPs were not selected.

The infiltration recommendation does not prohibit the implementation of permeable pavers to reduce the impervious area and DCV of the project. The paver section will conform with the draft County standard section for permeable pavers, likely utilizing the version with a raised subdrain.

Lined biofiltration BMPs are proposed to meet treatment control requirements for the project.

For the frontage improvements to the south of the high point in Mission Road, only water quality mitigation is required, as this portion drains to the HMP exempt system. Treatment control requirements for this area will be satisfied via implementation of tree wells, sized per County criteria.

The frontage improvements north of the high point are subject to both treatment control and flow control requirements and will require the implementation of a multiplying factor (1.6 multiplier for NRCS Soil Type A, and a 30-inch deep tree well) to determine the HMP DCV. An estimate has been provided for this discretionary phase of the project, as discussions with the County Traffic Department are ongoing as to the required width of the improvement in this area.

On Worksheet B.1-1, Row 44, it is demonstrated that no additional treatment is required, as the tree wells within DMA 6 and DMA 7 capture the entire DCV and HMP DCV, respectively.

The overall drainage area from the project site to the northerly discharge point, decreases from 1.9 acres, to 1.05 acres. Since the 1.05 acres that drain north in the developed condition are entirely pervious, there is an overall reduction in flow frequency to this Point of Compliance. Formal flow control calculations are therefore not provided for this POC.

Please refer to Attachments 1 and 2 for sizing calculations.

7.2.2 Structural BMP Summary Table (Complete for all proposed structural BMPs)

- List and provide the information requested below for all pollutant control and hydromodification management BMPs proposed for the project.
- For each BMP listed, complete the Structural BMP Checklist on the next page. Copy the Checklist as many times as needed.

				S	tructu	ral BM	1P Tvn	e		
			Structural BMP Type							
BMP ID#	DMA #	DMA Area (ft²)	Harvest and Use	Infiltration	Unlined Biofiltration	Lined Biofiltration	Flow-thru treatment	Hydromodification Management ¹	Other	Permit # and Sheet #
1	1	55,181				\boxtimes				
2	2	24,378				\boxtimes				
3	3	37,289							\boxtimes	
6	6	14,763							\boxtimes	

Copy and Paste table here for additional BMPs

¹ Hydromodification Management BMPs must be accompanied by BMPs that provide pollutant control.

7.3 Structural BMP Checklist (Complete once for each proposed structural BMP)

Structural BMP ID # 1 & 2		Permit # an	d Sheet #			
BMP Type						
Infiltration		Harvest and	l Use			
☐ Infiltration basin (INF-1)		☐ Cistern (1	HU-1)			
☐ Bioretention (INF-2)		Flow-thru T	reatment	(describe bel	ow)	
☐ Permeable pavement (INF-3)				•	et earlier PDP	
Unlined Biofiltration		requirem	-	1		
☐ Biofiltration with partial retention (PI	R-1)				site retention	
Lined Biofiltration			ation BMP ²			
☑ Biofiltration (BF-1)		☐ With alte		_		
☐ Nutrient Sensitive Media Design (BF-2	2)	Hydromodi		•		
☐ Proprietary Biofiltration (BF-3)		☐ Detention	n pond or va	ault		
		□ Other (de	scribe belo	w)		
BMP Purpose						
☑ Pollutant control only			•	ay for anothe	er BMP	
☐ Hydromodification control only		☐ Other (describe below)				
☐ Combined pollutant control and						
hydromodification						
BMP Verification (See BMPDM Section 8 Provide name and contact information						
for the party responsible to sign BMP	TBD					
verification forms						
BMP Ownership and Maintenance (See	RMPD	M Section 7.	3 and Attac	hment 11)		
BMP Maintenance Category		at. 1	Cat. 2	Cat. 3	Cat. 4	
		\boxtimes				
Final owner of BMP	□но	A	☑ Proper	ty Owner	☐ County	
	□ Oth	er (describe):			
Maintenance of BMP into perpetuity	□но	A	☑ Proper	ty Owner	☐ County	
	□ Other (describe):					
Discussion (As needed; Continue on sub-	sequen	t pages as ne	ecessary)			

² Indicate which onsite retention or biofiltration BMP the pre-treatment/forebay serves.

³ Hydromodification Management BMPs must be accompanied by BMPs that provide pollutant control.

Structural BMP ID # 3 & 6		Permit # an	d Sheet #				
BMP Type							
Infiltration		Harvest and	l Use				
☐ Infiltration basin (INF-1)		☐ Cistern (1	HU-1)				
☐ Bioretention (INF-2)		Flow-thru T	reatment (describe belo	ow)		
☐ Permeable pavement (INF-3)			•		et earlier PDP		
Unlined Biofiltration		requirem		10 7011 00 1110			
\square Biofiltration with partial retention (PF	R-1)	☐ Pre-treatment/forebay for an onsite retention					
Lined Biofiltration			ration BMP ²				
☐ Biofiltration (BF-1)		☐ With alte	rnative comp	pliance			
☐ Nutrient Sensitive Media Design (BF-2	2)	Hydromodi	fication Mai	nagement ³			
☑ Proprietary Biofiltration (BF-3)	,	☐ Detention	n pond or va	ult			
		□ Other (de	scribe below	<i>i</i>)			
BMP Purpose							
☑ Pollutant control only		☐ Pre-treat	ment/foreba	y for anothe	r BMP		
☐ Hydromodification control only		☐ Other (describe below)					
☐ Combined pollutant control and							
hydromodification							
BMP Verification (See BMPDM Section 8	-						
Provide name and contact information	TBD						
for the party responsible to sign BMP verification forms							
	DMDI	M Coation 7	2 and Attach	mont 11)			
BMP Ownership and Maintenance (See BMP Maintenance Category		Cat. 1	Cat. 2	Cat. 3	Cat. 4		
Bill Maintenance dategory	`	\					
Final owner of BMP	□но		□ Property	v Owner	□ County		
		her (describe		,			
Maintenance of BMP into perpetuity	□но	•	✓ Property	y Owner	☐ County		
	□ Ot	her (describe):		,		
Discussion BMP 3 is an onsite Filterra Pr	opriet	tary Biofiltrat	ion system (BF-3), sized	to treat 1.5		
times the Q85 for DMA 3.							
PMD 6 is an offsita Filtarra Dronziatary Pi	ofiltra	ntion system (DE 2) requi	rad to treat	1 E times the		
BMP 6 is an offsite Filterra Proprietary Biofiltration system (BF-3), required to treat 1.5 times the Q85 for DMA 6, and is actually sized to treat almost three times (3x) that flowrate to offset							
incidental pavement replacement that ma							
area drains to the BMP, and a quantitative	-	-		_			
provided in the engineering phase.							

² Indicate which onsite retention or biofiltration BMP the pre-treatment/forebay serves.

³ Hydromodification Management BMPs must be accompanied by BMPs that provide pollutant control.

7.4 Storm Water Pollutant Control Worksheet Calculations

- Use this page as a cover sheet for the submittal of any required worksheets below.
- Complete the checklist to identify which BMPDM Appendix B (Storm Water Pollutant Control Hydrologic Calculations and Sizing Methods) worksheets are included with this attachment.
- See BMPDM Appendix B for an explanation of the applicability of individual worksheets and detailed guidance on their completion.

Worksheet	Requirement
☑ Worksheet B.1 Calculation of Design Capture Volume (DCV)	Required
☑ Worksheet B.2 Retention Requirements	Required
☑ Worksheet B.3 BMP Performance	Required
☐ Worksheet B.4 Major Maintenance Intervals for Reduced-sized BMPs	If applicable
□ Other worksheets	As required

County of San Diego SWQMP Sub-attachment 7.4 (Pollutant Control Worksheet) Page 7.4-1 Template Date: January 03, 2019 Preparation Date: 2/7/2020

Automated Worksheet B.1-1: Calculation of Design Capture Volume (V1.3)

0	ш	Automated Work	Sheet D.1-1	: Calculatio	-	Capture v	orume (v 1.						TT *
Category	#	Description	1	11	iii	w	v	vi	vii	viii	ix	\mathcal{X}	Units
	0	Drainage Basin ID or Name	DMA 1	DMA 2	DMA 3	DMA 4		DMA 6	DMA 7				unitless
	1	Basin Drains to the Following BMP Type	Biofiltration	Biofiltration	Flow-Thru	Retention		Flow-Thru	n/a				unitless
	2	85th Percentile 24-hr Storm Depth	0.70	0.70	0.70	0.70		0.70	1.12				inches
0, 1, 1	3	Design Infiltration Rate Recommended by Geotechnical Engineer	0.000	0.000	0.000	0.025		-	-				in/hr
Standard Drainage Basin	4	Impervious Surfaces Not Directed to Dispersion Area (C=0.90)	36,784	15,657	30,771	2,328		7,065	6,066				sq-ft
Inputs	5	Semi-Pervious Surfaces Not Serving as Dispersion Area (C=0.30)											sq-ft
Inputs	6	Engineered Pervious Surfaces Not Serving as Dispersion Area (C=0.10)	18,397	8,721	6,518	23,380		7,698	2,155				sq-ft
	7	Natural Type A Soil Not Serving as Dispersion Area (C=0.10)											sq-ft
	8	Natural Type B Soil Not Serving as Dispersion Area (C=0.14)											sq-ft
	9	Natural Type C Soil Not Serving as Dispersion Area (C=0.23)											sq-ft
	10	Natural Type D Soil Not Serving as Dispersion Area (C=0.30)											sq-ft
	11	Does Tributary Incorporate Dispersion, Tree Wells, and/or Rain Barrels?	No	No	No	No		No	Yes				yes/no
	12	Impervious Surfaces Directed to Dispersion Area per SD-B (Ci=0.90)											sq-ft
	13	Semi-Pervious Surfaces Serving as Dispersion Area per SD-B (Ci=0.30)											sq-ft
	14	Engineered Pervious Surfaces Serving as Dispersion Area per SD-B (Ci=0.10)											sq-ft
Dispersion	15	Natural Type A Soil Serving as Dispersion Area per SD-B (Ci=0.10)											sq-ft
Area, Tree Well	16	Natural Type B Soil Serving as Dispersion Area per SD-B (Ci=0.14)											sq-ft
& Rain Barrel	17	Natural Type C Soil Serving as Dispersion Area per SD-B (Ci=0.23)											sq-ft
Inputs (Optional)	18	Natural Type D Soil Serving as Dispersion Area per SD-B (Ci=0.30)											sq-ft
(Optional)	19	Number of Tree Wells Proposed per SD-A							2				#
	20	Average Mature Tree Canopy Diameter							25				ft
	21	Number of Rain Barrels Proposed per SD-E											#
	22	Average Rain Barrel Size											gal
	23	Does BMP Overflow to Stormwater Features in <u>Downstream</u> Drainage?	No	No	No	No		No	No				unitless
Treatment	24	Identify Downstream Drainage Basin Providing Treatment in Series											unitless
Train Inputs &	25	Percent of Upstream Flows Directed to Downstream Dispersion Areas											percent
Calculations	26	Upstream Impervious Surfaces Directed to Dispersion Area (Ci=0.90)	0	0	0	0	0	0	0	0	0	0	cubic-feet
	27	Upstream Impervious Surfaces Not Directed to Dispersion Area (C=0.90)	0	0	0	0	0	0	0	0	0	0	cubic-feet
	28	Total Tributary Area	55,181	24,378	37,289	25,708	0	14,763	8,221	0	0	0	sq-ft
Initial Runoff	29	Initial Runoff Factor for Standard Drainage Areas	0.63	0.61	0.76	0.17	0.00	0.48	0.69	0.00	0.00	0.00	unitless
Factor	30	Initial Runoff Factor for Dispersed & Dispersion Areas	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	unitless
Calculation	31	Initial Weighted Runoff Factor	0.63	0.61	0.76	0.17	0.00	0.48	0.69	0.00	0.00	0.00	unitless
	32	Initial Design Capture Volume	2,028	867	1,653	255	0	413	529	0	0	0	cubic-feet
	33	Total Impervious Area Dispersed to Pervious Surface	0	0	0	0	0	0	0	0	0	0	sq-ft
D: :	34	Total Pervious Dispersion Area	0	0	0	0	0	0	0	0	0	0	sq-ft
Dispersion	35	Ratio of Dispersed Impervious Area to Pervious Dispersion Area	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	ratio
Area Adjustments	36	Adjustment Factor for Dispersed & Dispersion Areas	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	ratio
Majustificitis	37	Runoff Factor After Dispersion Techniques	0.63	0.61	0.76	0.17	n/a	0.48	0.69	n/a	n/a	n/a	unitless
	38	Design Capture Volume After Dispersion Techniques	2,028	867	1,653	255	0	413	529	0	0	0	cubic-feet
Tree & Barrel	39	Total Tree Well Volume Reduction	0	0	0	0	0	0	580	0	0	0	cubic-feet
Adjustments	40	Total Rain Barrel Volume Reduction	0	0	0	0	0	0	0	0	0	0	cubic-feet
	41	Final Adjusted Runoff Factor	0.63	0.61	0.76	0.17	0.00	0.48	0.00	0.00	0.00	0.00	unitless
Results	42	Final Effective Tributary Area	34,764	14,871	28,340	4,370	0	7,086	0	0	0	0	sq-ft
Results	43	Initial Design Capture Volume Retained by Site Design Elements	0	0	0	0	0	0	580	0	0	0	cubic-feet
	44	Final Design Capture Volume Tributary to BMP	2,028	867	1,653	255	0	413	0	0	0	0	cubic-feet
Warlsahaat D 1 1		· · · · · · · · · · · · · · · · · · ·		•									

Worksheet B.1-1 General Notes:

A. Applicants may use this worksheet to calculate design capture volumes for up to 10 drainage areas User input must be provided for yellow shaded cells, values for all other cells will be automatically generated, errors/notifications will be highlighted in red and summarized below. Upon completion of this worksheet, proceed to the appropriate BMP Sizing worksheet(s).

Automated Worksheet B.4-1: Sizing Retention BMPs (V1.3)

Catagogg	#	Description	;	ii.	iii	iv	(, _,,	avi.	vii	viii	ine		Units
Category		•	l	22	111	**	v	vi	vii	viii	ix	Х	
	0	Drainage Basin ID or Name	-	-	-	DMA 4	-	-	-	-	-	-	unitless
	1	Design Infiltration Rate Recommended by Geotechnical Engineer	-	-	-	0.025	-	-	1	-	-	-	in/hr
	2	Design Capture Volume Tributary to BMP	-	-	-	255	-	-	-	-	-	-	cubic-feet
BMP Inputs	3	Is Retention BMP Vegetated or Non-Vegetated?				Non-Vegetated							unitless
Divir Inputs	4	Provided Surface Area				23,379							sq-ft
	5	Provided Surface Ponding Depth				0							inches
	6	Provided Soil Media Thickness				0							inches
	7	Provided Gravel Storage Thickness				2							inches
	8	Volume Infiltrated Over 6 Hour Storm	0	0	0	255	0	0	0	0	0	0	cubic-feet
	9	Soil Media Pore Space	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	unitless
	10	Gravel Pore Space	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	unitless
T (*1)	11	Effective Depth of Retention Storage	0.0	0.0	0.0	0.8	0.0	0.0	0.0	0.0	0.0	0.0	inches
Infiltration Calculations	12	Drawdown Time for Surface Ponding (Post-Storm)	0	0	0	0	0	0	0	0	0	0	hours
	13	Drawdown Time for Entire Basin (Including 6 Hour Storm)	0	0	0	38	0	0	0	0	0	0	hours
	14	Volume Retained by BMP	0	0	0	1,814	0	0	0	0	0	0	cubic-feet
	15	Fraction of DCV Retained	0.00	0.00	0.00	3.00	0.00	0.00	0.00	0.00	0.00	0.00	ratio
	16	Percentage of Performance Requirement Satisfied	0.00	0.00	0.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	ratio
	17	Fraction of DCV Retained (normalized to 36-hr drawdown)	0.00	0.00	0.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	ratio
	18	This BMP Overflows to the Following Drainage Basin	-	-	-	-	-	-	-	-	-	-	unitless
Result	19	Deficit of Effectively Treated Stormwater	n/a	n/a	n/a	0	n/a	n/a	n/a	n/a	n/a	n/a	cubic-feet

Worksheet B.4-1 General Notes:

A. Applicants may use this worksheet to size Infiltration, Bioretention, and/or Permeable Pavement BMPs (INF-1, INF-2, INF-3) for up to 10 basins. User input must be provided for yellow shaded cells, values for blue cells are automatically populated based on user inputs from previous worksheets, values for all other cells will be automatically generated, errors/notifications will be highlighted in red/orange and summarized below. BMPs fully satisfying the pollutant control performance standards will have a deficit treated volume of zero and be highlighted in green.

Automated Worksheet B.5-1: Sizing Lined or Unlined Biofiltration BMPs (V1.3)

		Automated Worksh	eet D. 5-1:	Sizing Line		d bioiiitrati	ion bimps (V 1.3)					
Category	#	Description	i	ii	iii	iv	v	vi	vii	viii	ix	χ	Units
	0	Drainage Basin ID or Name	DMA 1	DMA 2	-	-	-	-	-	-	-	-	sq-ft
	1	Design Infiltration Rate Recommended by Geotechnical Engineer	0.000	0.000	-	-	-	-	-	-	-	-	in/hr
	2	Effective Tributary Area	34,764	14,871	-	-	-	-	-	-	-	-	sq-ft
	3	Minimum Biofiltration Footprint Sizing Factor	0.030	0.030	-	-	-	-	-	-	-	-	ratio
	4	Design Capture Volume Tributary to BMP	2,028	867	-	-	-	-	-	-	-	-	cubic-feet
BMP Inputs	5	Is Biofiltration Basin Impermeably Lined or Unlined?	Lined	Lined									unitless
Divir Imputs	6	Provided Biofiltration BMP Surface Area	1,860	500									sq-ft
	7	Provided Surface Ponding Depth	6	6									inches
	8	Provided Soil Media Thickness	18	18									inches
	9	Provided Depth of Gravel Above Underdrain Invert	12	12									inches
	10	Diameter of Underdrain or Hydromod Orifice (Select Smallest)	4.00	4.00									inches
	11	Provided Depth of Gravel Below the Underdrain	3	3									inches
	12	Volume Infiltrated Over 6 Hour Storm	0	0	0	0	0	0	0	0	0	0	cubic-feet
	13	Soil Media Pore Space Available for Retention	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	unitless
	14	Gravel Pore Space Available for Retention	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	unitless
	15	Effective Retention Depth	0.90	0.90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	inches
Retention	16	Calculated Retention Storage Drawdown (Including 6 Hr Storm)	120	120	0	0	0	0	0	0	0	0	hours
Calculations	17	Volume Retained by BMP	140	38	0	0	0	0	0	0	0	0	cubic-feet
	18	Fraction of DCV Retained	0.07	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	ratio
	19	Portion of Retention Performance Standard Satisfied	0.08	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	ratio
	20	Fraction of DCV Retained (normalized to 36-hr drawdown)	0.04	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	ratio
	21	Design Capture Volume Remaining for Biofiltration	1,947	850	0	0	0	0	0	0	0	0	cubic-feet
	22	Max Hydromod Flow Rate through Underdrain	0.7073	0.7073	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	CFS
	23	Max Soil Filtration Rate Allowed by Underdrain Orifice	16.43	61.11	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	in/hr
	24	Soil Media Filtration Rate per Specifications	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	in/hr
	25	Soil Media Filtration Rate to be used for Sizing	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	in/hr
	26	Depth Biofiltered Over 6 Hour Storm	30.00	30.00	30.00	30.00	30.00	30.00	30.00	30.00	30.00	30.00	inches
	27	Soil Media Pore Space Available for Biofiltration	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	unitless
Biofiltration	28	Effective Depth of Biofiltration Storage	14.40	14.40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	inches
Calculations	29	Drawdown Time for Surface Ponding	1	1	0	0	0	0	0	0	0	0	hours
Calculations	30	Drawdown Time for Effective Biofiltration Depth	3	3	0	0	0	0	0	0	0	0	hours
	31	Total Depth Biofiltered	44.40	44.40	30.00	30.00	30.00	30.00	30.00	30.00	30.00	30.00	inches
	32	Option 1 - Biofilter 1.50 DCV: Target Volume	2,921	1,275	0	0	0	0	0	0	0	0	cubic-feet
	33	Option 1 - Provided Biofiltration Volume	2,921	1,275	0	0	0	0	0	0	0	0	cubic-feet
	34	Option 2 - Store 0.75 DCV: Target Volume	1,460	638	0	0	0	0	0	0	0	0	cubic-feet
	35	Option 2 - Provided Storage Volume	1,460	600	0	0	0	0	0	0	0	0	cubic-feet
	36	Portion of Biofiltration Performance Standard Satisfied	1.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	ratio
	37	Do Site Design Elements and BMPs Satisfy Annual Retention Requirements?	Yes	Yes	-	-	-	-	-	-	-	-	yes/no
Result	38	Overall Portion of Performance Standard Satisfied	1.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	ratio
- Kesuit	39	This BMP Overflows to the Following Drainage Basin	-	-	-	-	-	-	-	-	-	-	unitless
	40	Deficit of Effectively Treated Stormwater	0	0	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	cubic-feet
Warlsahaat D. E.		•				-	•	•	•	•	•		

Worksheet B.5-1 General Notes:

A. Applicants may use this worksheet to size Lined or Unlined Biofiltration BMPs (BF-1, PR-1) for up to 10 basins. User input must be provided for yellow shaded cells, values for blue cells are automatically populated based on user inputs from previous worksheets, values for all other cells will be automatically generated, errors/notifications will be highlighted in red/orange and summarized below. BMPs fully satisfying the pollutant control performance standards will have a deficit treated volume of zero and be highlighted in green.

7.5 Identification and Narrative of Receiving Water and Pollutants of Concern

• Complete this sub-attachment *only if flow-thru treatment BMPs are implemented onsite* in lieu of retention or biofiltration BMPs. Unless excepted because of a Prior Lawful Approval⁴, PDPs must also participate in an alternative compliance program⁵.

A. General Description								
Describe flow path of storm water from the project site discharge location(s), through urban storm								
conveyance systems as applicable, to receiving creeks, rivers, and lagoons as applicable, and								
ultimate discharge to the Pacific Ocean (or bay, lagoon, lake or reservoir, as applicable).								
B. Water Body Impairments an								
List any 303(d) impaired water b								
Pacific Ocean (or bay, lagoon, lake		, <u> </u>	() (
causing impairment, and identify	any TMDLs and/or Hi	ghest Priority Pollut	ants from the WQIP for					
the impaired water bodies:								
000(1) I I I I I I I I I I I I I I I I I I I	D. II () /G.		TMDLs / WQIP					
303(d) Impaired Water Body	Pollutant(s)/Stre	SSOigh	est Priority Pollutant					
	, <u>`</u> C	,r· —						
C. Identification of Project Site	Pollutant							
Identify pollutants expected from		on all proposed use	(s) of the site (see BMP					
Design Manual Appendix B.6.	tille p	on an proposed ase	(3) of the site (see Divil					
2 001811 1 unioun 1 1 p 0 1 uni 1 2 1 0 1		A . 11 - 1 1 C	Alexandra de la TAZATA					
Dellestant	cable to	Anticipated from	Also a Receiving Water					
Pollutant	✓ roject Site	the Project Site	Pollutant of Concern					
Sediment								
Nutrients								
Heavy Metals								
Organic Compounds								
m l. 0 D . l								
Trash & Debris								
Oxygen Demanding Substances								
	_	-	1					
Oxygen Demanding Substances								

County of San Diego SWQMP Sub-attachment 7.5 (Pollutants of Concern) Page 7.5-1 Template Date: January 03, 2019 Preparation Date: 2/25/2019

⁴ See BMPDM Appendix L: Prior Lawful Approval Requirements and Guidance.

⁵ See SWQMP Attachment 12 (Alternative Compliance Projects) and BMPDM Appendix J (Offsite Alternative Compliance Requirements and Guidance).

⁶ The current list of Section 303(d) impaired water bodies can be found at: https://www.waterboards.ca.gov/water issues/programs/tmdl/integrated2014_2016.shtml



County of San Diego Stormwater Quality Management Plan (SWQMP)

Attachment 8: Documentation of DMAs with Structural Hydromodification BMPs

8.0 General Requirements

- Completion of this attachment is required for all PDPs subject to hydromodification management requirements (see PDP SWQMP Form Table 5). Do not submit this attachment if exempt from Hydromodification Management requirements. Document the PDP exemption in Attachment 9.
- Submit this cover page and all required Sub-attachments for all structural hydromodification management BMPs proposed for the project.
- Constructed features must <u>fully</u> satisfy the requirements described in applicable BMPDM sections and appendices, and any other guidance identified by the County.
- <u>DMA Exhibits and Construction Plans</u>: DMAs, features, and BMPs identified and described in this
 attachment must be shown on DMA Exhibits and all applicable construction plans submitted for
 the project. See Attachment 2 for additional instruction on exhibits and plans.
- <u>Structural BMP Certification</u>. All structural hydromodification management BMPs documented this attachment must be certified by a registered engineer in Attachment 7, Sub-attachment 7.1.
- <u>Structural BMP Verification</u>. BMP installation must be verified by the County at the completion of construction. Applicants must complete an Installation Verification Form (Attachment 10).

Sub-attachments (check all that are completed)						
⊠ 8.1: Flow Control Facility Design (required)¹						
Submit using the Sub-attachment 8.1 cover sheet provided, or □ as a separate stand-alone document labeled Sub-attachment 8.1.						
図 8.2: Hydromodification Management Points of Compliance (required)						
Complete the table provided in Sub-attachment 8.2.						
8.3: Geomorphic Assessment of Receiving Channels						
1. Has a geomorphic assessment been performed for the receiving channel(s)?						
☑ No, the low flow threshold is 0.1Q2 (default low flow threshold)						
☐ Yes (provide the information below):						
Low flow threshold: \square 0.1Q2 \square 0.3Q2 \square 0.5Q2						
Title:						
Date: Preparer:						
Submit using \square the Sub-attachment 8.3 cover sheet provided, or \square as a separate stand-alone						
document labeled Sub-attachment 8.3.						
8.4: Vector Control Plan (required if BMPs will not drain in less than 96 hours)						
☐ Included with this attachment ☒ Not required						

County of San Diego SWQMP Attachment 8.0 (General Requirements)

Page 8.0-1
Template Date: January 8, 2019

Preparation Date: 2/7/2020

¹ Including Structural BMP Drawdown Calculations and Overflow Design Summary. See BMPDM Chapter 6 and Appendix G for additional design guidance.

8.1 Flow Control Facility Design

Insert Flow Control Facility Design behind this cover page or submit as a separate stand-alone document labeled Sub-attachment 8.1. Flow control is only required for DMA 7, draining to the northerly POC, as the southerly portion of
the project drains to an HMP Exempt POC, directly discharging to the San Luis Rey River.
Flow control is accomplished by using the Tree Well multiplying factors for the DMA's soil type and the proposed tree well depth. Please refer to Attachment 1e for sizing calculations, wherein the typical D85 is multiplied by the multiplying factor to ensure the appropriate flow control volume is provided by the tree wells.
The multiplying factor of 1.6 has been selected for this DMA.

8.2 Hydromodification Management Points of Compliance

- List and describe all points of compliance (POCs) for flow control for hydromodification management.
- For each POC, provide a POC identification name or number, and a receiving channel identification name or number correlating to the project's HMP Exhibit (see Attachment 2).

POC name or #	Channel name or #	POC Description
2	SLR tributary	POC 2 is an unnamed tributary approximately 400 feet north/northeast of the project boundary. Project flow drain overland on the existing Mission Road to the POC.



NOT APPLICABLE

County of San Diego SWQMP Sub-attachment 9.4 (No Net Impact Analysis)

Page 9.4-1
Template Date: January 11, 2019

Preparation Date: 2/22/2019

This form must be accepted by the County prior to the release of construction permits or granting of occupancy for applicable portions of a Priority Development Project (PDP). Its purpose is to provide documentation of the final installation of permanent Best Management Practices (BMPs) used to satisfy Structural Performance Standards for the development project. Compliance with these standards reduces the discharge of pollutants and flows from the completed project site. Applicable standards may be satisfied using Structural BMPs (S-BMPs), Significant Site Design BMPs (SSD-BMPs), or both. Applicants are responsible for providing all requested information. Do not leave any fields blank; indicate *N/A* for any requested item that is not applicable.

PART 1 General Project and Applicant Information

Table 1: Project and Applicant Information

A. Project Summary Information		ID No. IVF-20 To be assigned by DPW-WPP				
Project Name	Caefield Senior Care Facility, Bor	sall				
Record ID (e.g., grading/improvement plan number, building permit)	Click here to enter text.					
Project Address	NE corner of Mission Avenue and Thoroughbred Lane					
Assessor's Parcel Number(s) APN(s))	126-230-55-00					
Project Watershed (complete Hydrologic Unit, Area, and Subarea Name with Numeric Identifier)	San Luis Rey, Lower San Luis Rey, Bonsall, 903.12					
B. Owner Information						
Name	Carefield Senior Living (Steven B	arklis)				
Address	201 Lomas Santa Fe Deive, Suite	450; Solana Beach, CA 92075				
Email Address	s svbark@aol.com					
Phone Number	Phone Number 858-259-5591					

Last updated: November 29, 2018 LUEG:SW PDP SWQMP – Attachments



County of San Diego Stormwater Quality Management Plan (SWQMP)

Attachment 11: BMP Maintenance Plans and Agreements

11.0 Cover Sheet and General Requirements

- All Structural BMPs must have a plan and mechanism to ensure on-going maintenance. Use the
 table below to document the types of agreements to be submitted for the PDP and submit them
 under cover of this sheet.
- See BMPDM Section 7.3 for a description of maintenance categories and responsibilities. Note that since Category 3 and 4 BMPs are County-maintained, they do not require maintenance agreements.

a. Applicability of Maintenance Agreements

Check the boxes below to indicate which types of agreements are included with this attachment.

☐ Maintenance Notification (Category 1 BMPs)

- Exhibit A: Project Site Vicinity; Project Site Map; and a map for each BMP and its Drainage Management Area
- Exhibit B: BMP Maintenance Plan (see below)
- ☐ Stormwater Maintenance Agreement (Category 2 BMPs)
 - Exhibit A: Legal Description of Property
 - Exhibit B: BMP Maintenance Plan (see below)
 - Exhibit C: Project Site Vicinity Map

Maintenance agreement templates and instructions are provided on the County's website:

www.sandiegocounty.gov/stormwater under the Development Resources tab.

PDP applicants contact County staff to ensure they have the most current forms.

b. Maintenance Plan Requirements

Use this checklist to confirm that each maintenance plan includes the following that as applicable.

- ⊠ Specific **maintenance indicators and actions** for proposed structural BMP(s). These must be based on based on maintenance indicators presented in BMP Design Fact Sheets in Appendix E and enhanced to reflect actual proposed components of the structural BMP(s).
- \boxtimes **Access** to inspect and perform maintenance on the structural BMP(s).
- ⊠ Features to **facilitate inspection** (e.g., observation ports, cleanouts, silt posts, or other features that allow the inspector to view necessary components of the structural BMP and compare to maintenance thresholds).
- \square Manufacturer and part number for **proprietary parts** of structural BMP(s) when applicable.
- ☑ **Maintenance thresholds** specific to the structural BMP(s), with a location-specific frame of reference (e.g., level of accumulated materials that triggers removal of the materials, to be identified based on viewing marks on silt posts or measured with a survey rod with respect to a fixed benchmark within the BMP).
- ⊠ Recommended **equipment** to perform maintenance.
- ☑ When applicable, necessary special **training or certification** requirements for inspection and maintenance personnel such as confined space entry or hazardous waste management.

County of San Diego SWQMP Attachment 11 Page 11.0-1
Template Date: December 28, 2018 Preparation Date: 2/25/2019

BMP MAINTENANCE FACT SHEET FOR STRUCTURAL BMP BF-1 BIOFILTRATION

Biofiltration facilities are vegetated surface water systems that filter water through vegetation, and soil or engineered media prior to discharge via underdrain or overflow to the downstream conveyance system. Biofiltration facilities have limited or no infiltration. They are typically designed to provide enough hydraulic head to move flows through the underdrain connection to the storm drain system. Typical biofiltration components include:

- Inflow distribution mechanisms (e.g., perimeter flow spreader or filter strips)
- Energy dissipation mechanism for concentrated inflows (e.g., splash blocks or riprap)
- Shallow surface ponding for captured flows
- Side slope and basin bottom vegetation selected based on climate and ponding depth
- Non-floating mulch layer
- Media layer (planting mix or engineered media) capable of supporting vegetation growth
- Filter course layer consisting of aggregate to prevent the migration of fines into uncompacted native soils or the aggregate storage layer
- Aggregate storage layer with underdrain(s)
- Impermeable liner or uncompacted native soils at the bottom of the facility
- Overflow structure

Normal Expected Maintenance

Biofiltration requires routine maintenance to: remove accumulated materials such as sediment, trash or debris; maintain vegetation health; maintain infiltration capacity of the media layer; replenish mulch; and maintain integrity of side slopes, inlets, energy dissipators, and outlets. A summary table of standard inspection and maintenance indicators is provided within this Fact Sheet.

Non-Standard Maintenance or BMP Failure

If any of the following scenarios are observed, the BMP is not performing as intended to protect downstream waterways from pollution and/or erosion. Corrective maintenance, increased inspection and maintenance, BMP replacement, or a different BMP type will be required.

- The BMP is not drained between storm events. Surface ponding longer than approximately 24 hours following a storm event may be detrimental to vegetation health, and surface ponding longer than approximately 96 hours following a storm event poses a risk of vector (mosquito) breeding. Poor drainage can result from clogging of the media layer, filter course, aggregate storage layer, underdrain, or outlet structure. The specific cause of the drainage issue must be determined and corrected.
- Sediment, trash, or debris accumulation greater than 25% of the surface ponding volume within one month. This means the load from the tributary drainage area is too high, reducing BMP function or clogging the BMP. This would require pretreatment measures within the tributary area draining to the BMP to intercept the materials. Pretreatment components, especially for sediment, will extend the life of components that are more expensive to replace such as media, filter course, and aggregate layers.
- Erosion due to concentrated storm water runoff flow that is not readily corrected by adding erosion control blankets, adding stone at flow entry points, or minor re-grading to restore proper drainage according to the original plan. If the issue is not corrected by restoring the BMP to the original plan and grade, the [City Engineer] shall be contacted prior to any additional repairs or reconstruction.

Other Special Considerations

Biofiltration is a vegetated structural BMP. Vegetated structural BMPs that are constructed in the vicinity of, or connected to, an existing jurisdictional water or wetland could inadvertently result in creation of expanded waters or wetlands. As such, vegetated structural BMPs have the potential to come under the jurisdiction of the United States Army Corps of Engineers, SDRWQCB, California Department of Fish and Wildlife, or the United States Fish and Wildlife Service. This could result in the need for specific resource agency permits and costly mitigation to perform maintenance of the structural BMP. Along with proper placement of a structural BMP, <u>routine</u> <u>maintenance</u> is key to preventing this scenario.

SUMMARY OF STANDARD INSPECTION AND MAINTENANCE FOR BF-1 BIOFILTRATION

The property owner is responsible to ensure inspection, operation and maintenance of permanent BMPs on their property unless responsibility has been formally transferred to an agency, community facilities district, homeowners association, property owners association, or other special district.

Maintenance frequencies listed in this table are average/typical frequencies. Actual maintenance needs are site-specific, and maintenance may be required more frequently. Maintenance must be performed whenever needed, based on maintenance indicators presented in this table. The BMP owner is responsible for conducting regular inspections to see when maintenance is needed based on the maintenance indicators. During the first year of operation of a structural BMP, inspection is recommended at least once prior to August 31 and then monthly from September through May. Inspection during a storm event is also recommended. After the initial period of frequent inspections, the minimum inspection and maintenance frequency can be determined based on the results of the first year inspections.

Threshold/Indicator	Maintenance Action	Typical Maintenance Frequency
Accumulation of sediment, litter, or debris	Remove and properly dispose of accumulated materials, without damage to the vegetation or compaction of the media layer.	 Inspect monthly. If the BMP is 25% full* or more in one month, increase inspection frequency to monthly plus after every 0.1-inch or larger storm event. Remove any accumulated materials found at each inspection.
Obstructed inlet or outlet structure	Clear blockage.	 Inspect monthly and after every 0.5-inch or larger storm event. Remove any accumulated materials found at each inspection.
Damage to structural components such as weirs, inlet or outlet structures	Repair or replace as applicable	Inspect annually. Maintenance when needed.
Poor vegetation establishment	Re-seed, re-plant, or re-establish vegetation per original plans.	Inspect monthly. Maintenance when needed.
Dead or diseased vegetation	Remove dead or diseased vegetation, re-seed, re-plant, or re-establish vegetation per original plans.	Inspect monthly. Maintenance when needed.
Overgrown vegetation	Mow or trim as appropriate.	Inspect monthly. Maintenance when needed.
2/3 of mulch has decomposed, or mulch has been removed	Remove decomposed fraction and top off with fresh mulch to a total depth of 3 inches.	Inspect monthly. Replenish mulch annually, or more frequently when needed based on inspection.

^{*&}quot;25% full" is defined as ¼ of the depth from the design bottom elevation to the crest of the outflow structure (e.g., if the height to the outflow opening is 12 inches from the bottom elevation, then the materials must be removed when there is 3 inches of accumulation – this should be marked on the outflow structure).

BF-1 Biofiltration

SUMMARY OF STANDARD INSPECTION AND MAINTENANCE FOR BF-1 BIOFILTRATION (Continued from previous page)			
Threshold/Indicator	·		
Erosion due to concentrated irrigation flow	Repair/re-seed/re-plant eroded areas and adjust the irrigation system.	Inspect monthly.Maintenance when needed.	
Erosion due to concentrated storm water runoff flow	Repair/re-seed/re-plant eroded areas, and make appropriate corrective measures such as adding erosion control blankets, adding stone at flow entry points, or minor re-grading to restore proper drainage according to the original plan. If the issue is not corrected by restoring the BMP to the original plan and grade, the [City Engineer] shall be contacted prior to any additional repairs or reconstruction.	 Inspect after every 0.5-inch or larger storm event. If erosion due to storm water flow has been observed, increase inspection frequency to after every 0.1-inch or larger storm event. Maintenance when needed. If the issue is not corrected by restoring the BMP to the original plan and grade, the [City Engineer] shall be contacted prior to any additional repairs or reconstruction. 	
Standing water in BMP for longer than 24 hours following a storm event Surface ponding longer than approximately 24 hours following a storm event may be detrimental to vegetation health	Make appropriate corrective measures such as adjusting irrigation system, removing obstructions of debris or invasive vegetation, clearing underdrains, or repairing/replacing clogged or compacted soils.	 Inspect monthly and after every 0.5-inch or larger storm event. If standing water is observed, increase inspection frequency to after every 0.1-inch or larger storm event. Maintenance when needed. 	
Presence of mosquitos/larvae For images of egg rafts, larva, pupa, and adult mosquitos, see http://www.mosquito.org/biology	If mosquitos/larvae are observed: first, immediately remove any standing water by dispersing to nearby landscaping; second, make corrective measures as applicable to restore BMP drainage to prevent standing water.	 Inspect monthly and after every 0.5-inch or larger storm event. If mosquitos are observed, increase inspection frequency to after every 0.1-inch or larger storm event. Maintenance when needed. 	
	If mosquitos persist following corrective measures to remove standing water, or if the BMP design does not meet the 96-hour drawdown criteria due to release rates controlled by an orifice installed on the underdrain, the [City Engineer] shall be contacted to determine a solution. A different BMP type, or a Vector Management Plan prepared with concurrence from the County of San Diego Department of Environmental Health, may be required.		
Underdrain clogged	Clear blockage.	 Inspect if standing water is observed for longer than 24-96 hours following a storm event. Maintenance when needed. 	

References

American Mosquito Control Association.

http://www.mosquito.org/

California Storm Water Quality Association (CASQA). 2003. Municipal BMP Handbook.

https://www.casqa.org/resources/bmp-handbooks/municipal-bmp-handbook

County of San Diego. 2014. Low Impact Development Handbook.

http://www.sandiegocounty.gov/content/sdc/dpw/watersheds/susmp/lid.html

San Diego County Copermittees. 2016. Model BMP Design Manual, Appendix E, Fact Sheet BF-1.

http://www.projectcleanwater.org/index.php?option=com_content&view=article&id=250&Itemid=220

Page Intentionally Blank for Double-Sided Printing

Date:	Inspector:			BMP ID No.:
Permit No.:	APN(s):			
Property / Development Name:		Responsib	le Party Name and	Phone Number:
Property Address of BMP:		Responsib	le Party Address:	
INSP	ECTION AND MAINTENANCE CHECKL	IST FOR BF-	1 BIOFILTRATION F	PAGE 1 of 5
Threshold/Indicator	Maintenance Recommendation	on	Date	Description of Maintenance Conducted
Accumulation of sediment, litter, or debris	☐ Remove and properly dispose of			
Maintenance Needed?	accumulated materials, without to the vegetation	damage		
□ YES □ NO □ N/A	 ☐ If sediment, litter, or debris accume xceeds 25% of the surface pond volume within one month (25% fladd a forebay or other pre-treatmeasures within the tributary and draining to the BMP to intercept materials. ☐ Other / Comments: 	ling full*), ment ea		
Poor vegetation establishment Maintenance Needed? YES NO N/A	□ Re-seed, re-plant, or re-establish vegetation per original plans□ Other / Comments:			

^{*&}quot;25% full" is defined as ¼ of the depth from the design bottom elevation to the crest of the outflow structure (e.g., if the height to the outflow opening is 12 inches from the bottom elevation, then the materials must be removed when there is 3 inches of accumulation – this should be marked on the outflow structure).

Date:	Inspector:	BMP ID No.:
Permit No.:	APN(s):	

INSPECTION AND MAINTENANCE CHECKLIST FOR BF-1 BIOFILTRATION PAGE 2 of 5			
Threshold/Indicator	Maintenance Recommendation	Date	Description of Maintenance Conducted
Dead or diseased vegetation	\square Remove dead or diseased vegetation, re-		
Maintenance Needed?	seed, re-plant, or re-establish vegetation per original plans		
☐ YES ☐ NO ☐ N/A	☐ Other / Comments:		
Overgrown vegetation	☐ Mow or trim as appropriate		
Maintenance Needed?	☐ Other / Comments:		
☐ YES ☐ NO ☐ N/A			
2/3 of mulch has decomposed, or mulch has been removed Maintenance Needed? ☐ YES ☐ NO ☐ N/A	 □ Remove decomposed fraction and top off with fresh mulch to a total depth of 3 inches □ Other / Comments: 		

Date:	Inspector:	BMP ID No.:
Permit No.:	APN(s):	

INSPECTION AND MAINTENANCE CHECKLIST FOR BF-1 BIOFILTRATION PAGE 3 of 5			
Threshold/Indicator	Maintenance Recommendation	Date	Description of Maintenance Conducted
Erosion due to concentrated irrigation flow Maintenance Needed? YES NO N/A	 □ Repair/re-seed/re-plant eroded areas and adjust the irrigation system □ Other / Comments: 		
Erosion due to concentrated storm water runoff flow Maintenance Needed? YES NO N/A	□ Repair/re-seed/re-plant eroded areas, and make appropriate corrective measures such as adding erosion control blankets, adding stone at flow entry points, or minor re-grading to restore proper drainage according to the original plan □ If the issue is not corrected by restoring the BMP to the original plan and grade, the [City Engineer] shall be contacted prior to any additional repairs or reconstruction □ Other / Comments:		

Date:	Inspector:	BMP ID No.:
Permit No.:	APN(s):	

INSPECTION AND MAINTENANCE CHECKLIST FOR BF-1 BIOFILTRATION PAGE 4 of 5			
Threshold/Indicator	Maintenance Recommendation	Date	Description of Maintenance Conducted
Obstructed inlet or outlet structure	☐ Clear blockage		
Maintenance Needed?	☐ Other / Comments:		
□ YES			
□NO			
□ N/A			
Underdrain clogged (inspect underdrain if	☐ Clear blockage		
standing water is observed for longer than 24-96 hours following a storm event)	☐ Other / Comments:		
	·		
Maintenance Needed?			
☐ YES			
\square NO			
□ N/A			
Damage to structural components such as weirs,	☐ Repair or replace as applicable		
inlet or outlet structures	☐ Other / Comments:		
Maintenance Needed?	- Cinci / Comments.		
☐ YES			
□ NO			
□ N/A			

Date:	Inspector:	BMP ID No.:
Permit No.:	APN(s):	

INSPECTION AND MAINTENANCE CHECKLIST FOR BF-1 BIOFILTRATION PAGE 5 of 5			
Threshold/Indicator	Maintenance Recommendation	Date	Description of Maintenance Conducted
Standing water in BMP for longer than 24-96 hours following a storm event* Surface ponding longer than approximately 24 hours following a storm event may be detrimental to vegetation health Maintenance Needed? YES NO N/A	□ Make appropriate corrective measures such as adjusting irrigation system, removing obstructions of debris or invasive vegetation, clearing underdrains, or repairing/replacing clogged or compacted soils		
Presence of mosquitos/larvae For images of egg rafts, larva, pupa, and adult mosquitos, see http://www.mosquito.org/biology Maintenance Needed? YES NO N/A	□ Apply corrective measures to remove standing water in BMP when standing water occurs for longer than 24-96 hours following a storm event.** □ Other / Comments:		

^{*}Surface ponding longer than approximately 24 hours following a storm event may be detrimental to vegetation health, and surface ponding longer than approximately 96 hours following a storm event poses a risk of vector (mosquito) breeding. Poor drainage can result from clogging of the media layer, filter course, aggregate storage layer, underdrain, or outlet structure. The specific cause of the drainage issue must be determined and corrected.

^{**}If mosquitos persist following corrective measures to remove standing water, or if the BMP design does not meet the 96-hour drawdown criteria due to release rates controlled by an orifice installed on the underdrain, the [City Engineer] shall be contacted to determine a solution. A different BMP type, or a Vector Management Plan prepared with concurrence from the County of San Diego Department of Environmental Health, may be required.